

Schema documentation for vast_2.0.1.xsd

9 march 2010

Table of Contents

Namespace: ""	2
Schemas	2
Main schema vast_2.0.1.xsd	2
Elements	3
Element VAST	3
Element VAST / Ad	8
Element Ad / VAST / InLine	13
Element InLine / Ad / VAST / AdSystem	16
Element InLine / Ad / VAST / AdTitle	17
Element InLine / Ad / VAST / Description	17
Element InLine / Ad / VAST / Survey	17
Element InLine / Ad / VAST / Error	18
Element InLine / Ad / VAST / Impression	18
Element InLine / Ad / VAST / Creatives	18
Element Creatives / InLine / Ad / VAST / Creative	21
Element Creative / Creatives / InLine / Ad / VAST / Linear	23
Element Linear / Creative / Creatives / InLine / Ad / VAST / Duration	25
Element Linear / Creative / Creatives / InLine / Ad / VAST / TrackingEvents	25
Element TrackingEvents_type / Tracking	25
Element Linear / Creative / Creatives / InLine / Ad / VAST / AdParameters	26
Element Linear / Creative / Creatives / InLine / Ad / VAST / VideoClicks	26
Element VideoClicks_type / ClickThrough	27
Element VideoClicks_type / CustomClick	28
Element Linear / Creative / Creatives / InLine / Ad / VAST / MediaFiles	28
Element MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / MediaFile	30
Element Creative / Creatives / InLine / Ad / VAST / CompanionAds	32
Element CompanionAds / Creative / Creatives / InLine / Ad / VAST / Companion	32
Element Companion_type / StaticResource	34
Element Companion_type / IFrameResource	34
Element Companion_type / HTMLResource	35
Element Companion_type / TrackingEvents	35
Element Companion_type / CompanionClickThrough	35
Element Companion_type / AltText	36
Element Companion_type / AdParameters	36
Element Creative / Creatives / InLine / Ad / VAST / NonLinearAds	36
Element NonLinearAds / Creative / Creatives / InLine / Ad / VAST / TrackingEvents	37
Element NonLinearAds / Creative / Creatives / InLine / Ad / VAST / NonLinear	37
Element NonLinear_type / StaticResource	39
Element NonLinear_type / IFrameResource	39
Element NonLinear_type / HTMLResource	40
Element NonLinear_type / NonLinearClickThrough	40
Element NonLinear_type / AdParameters	40
Element InLine / Ad / VAST / Extensions	41
Element Extensions / InLine / Ad / VAST / Extension	41
Element Ad / VAST / Wrapper	41
Element Wrapper / Ad / VAST / AdSystem	43
Element Wrapper / Ad / VAST / VASTAdTagURI	44
Element Wrapper / Ad / VAST / Error	44
Element Wrapper / Ad / VAST / Impression	44
Element Wrapper / Ad / VAST / Creatives	45
Element Creatives / Wrapper / Ad / VAST / Creative	46
Element Creative / Creatives / Wrapper / Ad / VAST / Linear	47
Element Linear / Creative / Creatives / Wrapper / Ad / VAST / TrackingEvents	48
Element Linear / Creative / Creatives / Wrapper / Ad / VAST / VideoClicks	48
Element VideoClicks / Linear / Creative / Creatives / Wrapper / Ad / VAST / ClickTracking	49
Element Creative / Creatives / Wrapper / Ad / VAST / CompanionAds	49
Element CompanionAds / Creative / Creatives / Wrapper / Ad / VAST / Companion	50
Element Creative / Creatives / Wrapper / Ad / VAST / NonLinearAds	51
Element NonLinearAds / Creative / Creatives / Wrapper / Ad / VAST / TrackingEvents	51
Element NonLinearAds / Creative / Creatives / Wrapper / Ad / VAST / NonLinear	52
Element Wrapper / Ad / VAST / Extensions	53

Element Extensions / Wrapper / Ad / VAST / Extension.....	54
Complex Types	54
Complex Type AdSystem_type	54
Complex Type Impression_type	54
Complex Type TrackingEvents_type	55
Complex Type VideoClicks_type	56
Complex Type Companion_type	56
Complex Type NonLinear_type	59
Attributes	61
Attribute AdSystem_type / @version	61
Attribute Impression_type / @id	61
Attribute Tracking / TrackingEvents_type / @event	61
Attribute ClickThrough / VideoClicks_type / @id	62
Attribute ClickTracking / VideoClicks_type / @id	62
Attribute CustomClick / VideoClicks_type / @id	62
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @id	63
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @delivery	63
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @type	63
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @bitrate	63
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @width	64
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @height	64
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @scalable	64
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @maintainAspectRatio	64
Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @apiFramework	65
Attribute StaticResource / Companion_type / @creativeType	65
Attribute Companion_type / @id	65
Attribute Companion_type / @width	65
Attribute Companion_type / @height	66
Attribute Companion_type / @expandedWidth	66
Attribute Companion_type / @expandedHeight	66
Attribute Companion_type / @apiFramework	66
Attribute StaticResource / NonLinear_type / @creativeType	67
Attribute NonLinear_type / @id	67
Attribute NonLinear_type / @width	67
Attribute NonLinear_type / @height	67
Attribute NonLinear_type / @expandedWidth	67
Attribute NonLinear_type / @expandedHeight	68
Attribute NonLinear_type / @scalable	68
Attribute NonLinear_type / @maintainAspectRatio	68
Attribute NonLinear_type / @minSuggestedDuration	68
Attribute NonLinear_type / @apiFramework	69
Attribute Creative / Creatives / InLine / Ad / VAST / @id	69
Attribute Creative / Creatives / InLine / Ad / VAST / @sequence	69
Attribute Creative / Creatives / InLine / Ad / VAST / @AdID	69
Attribute ClickTracking / VideoClicks / Linear / Creative / Creatives / Wrapper / Ad / VAST / @id	69
Attribute Creative / Creatives / Wrapper / Ad / VAST / @id	70
Attribute Creative / Creatives / Wrapper / Ad / VAST / @sequence	70
Attribute Creative / Creatives / Wrapper / Ad / VAST / @AdID	70
Attribute Ad / VAST / @id	70
Attribute VAST / @version	70

Namespace: ""

Schemas

Main schema vast_2.0.1.xsd

Namespace	No namespace
Properties	attribute form default: unqualified element form default: qualified

Elements

Element VAST

Namespace	No namespace														
Annotations	IAB VAST, Video Ad Serving Template, video xml ad response, Version 2.0.1, xml schema prepared by Tremor Media														
Diagram	<pre> classDiagram class VAST { @version Type xs:string } class Ad VAST "0..infinity" --> Ad </pre>														
Properties	content: complex														
Model	Ad*														
Children	Ad														
Instance	<VAST version=""> <Ad id="">{0,unbounded}</Ad> </VAST>														
Attributes	<table border="1"> <thead> <tr> <th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th></tr> </thead> <tbody> <tr> <td>version</td><td>xs:string</td><td></td><td></td><td>required</td></tr> </tbody> </table> <p>Current version is 2.0. The 2.0.1 version corrects an error in the Wrapper section related the Linear node's TrackingEvents and VideoClicks elements.</p>					QName	Type	Fixed	Default	Use	version	xs:string			required
QName	Type	Fixed	Default	Use											
version	xs:string			required											
Source	<pre> <xss:element name="VAST"> <xss:annotation> <xss:documentation>IAB VAST, Video Ad Serving Template, video xml ad response, Version 2.0.1, xml schema prepared by Tremor Media</xss:documentation> </xss:annotation> <xss:complexType> <xss:sequence> <xss:element name="Ad" maxOccurs="unbounded" minOccurs="0"> <xss:annotation> <xss:documentation>Top-level element, wraps each ad in the response</xss:documentation> </xss:annotation> <xss:complexType> <xss:choice maxOccurs="1" minOccurs="1"> <xss:element name="InLine" maxOccurs="1" minOccurs="0"> <xss:annotation> <xss:documentation>Second-level element surrounding complete ad data for a single ad</xss:documentation> </xss:annotation> <xss:complexType> <xss:sequence> <xss:element name="AdSystem" maxOccurs="1" minOccurs="1" type="AdSystem_type"> <xss:annotation> <xss:documentation>Indicates source ad server</xss:documentation> </xss:annotation> </xss:element> <xss:element name="AdTitle" type="xs:string" maxOccurs="1" minOccurs="1"> <xss:annotation> <xss:documentation>Common name of ad</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Description" type="xs:string" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>Longer description of ad</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Survey" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>URL of request to survey vendor</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>URL to request if ad does not play due to error</xss:documentation> </xss:annotation> </xss:element> </xss:sequence> </xss:complexType> </xss:choice> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:annotation> </xss:element> </pre>														

 | | | |

Namespace	No namespace														
Annotations	IAB VAST, Video Ad Serving Template, video xml ad response, Version 2.0.1, xml schema prepared by Tremor Media														
Diagram	<pre> classDiagram class VAST { @version Type xs:string } class Ad VAST "0..infinity" --> Ad </pre>														
Properties	content: complex														
Model	Ad*														
Children	Ad														
Instance	<VAST version=""> <Ad id="">{0,unbounded}</Ad> </VAST>														
Attributes	<table border="1"> <thead> <tr> <th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th></tr> </thead> <tbody> <tr> <td>version</td><td>xs:string</td><td></td><td></td><td>required</td></tr> </tbody> </table> <p>Current version is 2.0. The 2.0.1 version corrects an error in the Wrapper section related the Linear node's TrackingEvents and VideoClicks elements.</p>					QName	Type	Fixed	Default	Use	version	xs:string			required
QName	Type	Fixed	Default	Use											
version	xs:string			required											
Source	<pre> <xss:element name="VAST"> <xss:annotation> <xss:documentation>IAB VAST, Video Ad Serving Template, video xml ad response, Version 2.0.1, xml schema prepared by Tremor Media</xss:documentation> </xss:annotation> <xss:complexType> <xss:sequence> <xss:element name="Ad" maxOccurs="unbounded" minOccurs="0"> <xss:annotation> <xss:documentation>Top-level element, wraps each ad in the response</xss:documentation> </xss:annotation> <xss:complexType> <xss:choice maxOccurs="1" minOccurs="1"> <xss:element name="InLine" maxOccurs="1" minOccurs="0"> <xss:annotation> <xss:documentation>Second-level element surrounding complete ad data for a single ad</xss:documentation> </xss:annotation> <xss:complexType> <xss:sequence> <xss:element name="AdSystem" maxOccurs="1" minOccurs="1" type="AdSystem_type"> <xss:annotation> <xss:documentation>Indicates source ad server</xss:documentation> </xss:annotation> </xss:element> <xss:element name="AdTitle" type="xs:string" maxOccurs="1" minOccurs="1"> <xss:annotation> <xss:documentation>Common name of ad</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Description" type="xs:string" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>Longer description of ad</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Survey" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>URL of request to survey vendor</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>URL to request if ad does not play due to error</xss:documentation> </xss:annotation> </xss:element> </xss:sequence> </xss:complexType> </xss:choice> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:annotation> </xss:element> </pre>														

 | | | |

```

        </xs:element>
        <xs:element name="Impression" type="Impression_type"
maxOccurs="unbounded" minOccurs="1">
            <xs:annotation>
                <xs:documentation>URL to track impression</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element maxOccurs="1" minOccurs="1" name="Creatives">
            <xs:annotation>
                <xs:documentation>Any number of companions in any desired pixel
dimensions.</xs:documentation>
            </xs:annotation>
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Creative" maxOccurs="unbounded">
                        <xs:annotation>
                            <xs:documentation>Wraps each creative element within an InLine
or Wrapper Ad</xs:documentation>
                        </xs:annotation>
                        <xs:complexType>
                            <xs:choice>
                                <xs:element name="Linear" minOccurs="0" maxOccurs="1">
                                    <xs:complexType>
                                        <xs:sequence>
                                            <xs:element name="Duration" type="xs:time"
maxOccurs="1" minOccurs="1">
                                                <xs:annotation>
                                                    <xs:documentation>Duration in standard time
format, hh:mm:ss</xs:documentation>
                                                </xs:annotation>
                                            </xs:element>
                                            <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
                                                <xs:element>
                                                    <xs:element name="AdParameters" type="xs:string"
minOccurs="0" maxOccurs="1">
                                                        <xs:annotation>
                                                            <xs:documentation>Data to be passed into the video
ad</xs:documentation>
                                                        </xs:annotation>
                                                    </xs:element>
                                                    <xs:element name="VideoClicks" minOccurs="0"
type="VideoClicks_type" maxOccurs="1">
                                                        <xs:element>
                                                            <xs:element name="MediaFiles" minOccurs="0"
maxOccurs="1">
                                                                <xs:complexType>
                                                                    <xs:sequence>
                                                                        <xs:element name="MediaFile" minOccurs="1"
maxOccurs="unbounded">
                                                                            <xs:annotation>
                                                                                <xs:documentation>Location of linear file</xs:documentation>
                                                                            </xs:annotation>
                                                                <xs:complexType>
                                                                <xs:simpleContent>
                                                                    <xs:extension base="xs:anyURI">
                                                                        <xs:attribute name="id" type="xs:string"
use="optional">
                                                                            <xs:annotation>
                                                                                <xs:documentation>Optional
identifier</xs:documentation>
                                                                            </xs:annotation>
                                                                        </xs:attribute>
                                                                        <xs:attribute name="delivery"
use="required">
                                                                            <xs:annotation>
                                                                                <xs:documentation>Method of delivery
of ad</xs:documentation>
                                                                            </xs:annotation>
                                                                <xs:simpleType>
                                                                <xs:restriction base="xs:NMTOKEN">
                                                                    <xs:enumeration value="streaming"/>
                                                                </xs:restriction>
                                                                </xs:simpleType>
                                                                </xs:attribute>
                                                                <xs:attribute name="type" use="required"
type="xs:string">
                                                                    <xs:annotation>

```

```

                <xs:documentation>MIME type. Popular
MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and
"video/x-flv" for Flash Video. Image ads or interactive ads can be included in the
MediaFiles section with appropriate Mime types</xs:documentation>
                </xs:annotation>
                </xs:attribute>
                <xs:attribute name="bitrate"
type="xs:integer" use="optional">
                <xs:annotation>
                    <xs:documentation>Bitrate of encoded
video in Kbps</xs:documentation>
                </xs:annotation>
                </xs:attribute>
                <xs:attribute name="width"
type="xs:integer" use="required">
                <xs:annotation>
                    <xs:documentation>Pixel dimensions
of video</xs:documentation>
                </xs:annotation>
                </xs:attribute>
                <xs:attribute name="height"
type="xs:integer" use="required">
                <xs:annotation>
                    <xs:documentation>Pixel dimensions
of video</xs:documentation>
                </xs:annotation>
                </xs:attribute>
                <xs:attribute name="scalable"
type="xs:boolean" use="optional">
                <xs:annotation>
                    <xs:documentation>Whether it is
acceptable to scale the image.</xs:documentation>
                </xs:annotation>
                </xs:attribute>
                <xs:attribute name="maintainAspectRatio"
type="xs:boolean" use="optional">
                <xs:annotation>
                    <xs:documentation>Whether the ad
must have its aspect ratio maintained when scales</xs:documentation>
                </xs:annotation>
                </xs:attribute>
                <xs:attribute name="apiFramework"
type="xs:string" use="optional">
                <xs:annotation>
                    <xs:documentation>The apiFramework
defines the method to use for communication if the MediaFile is interactive. Suggested
values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for
Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset
request).</xs:documentation>
                </xs:annotation>
                </xs:attribute>
                </xs:extension>
                </xs:simpleContent>
            </xs:complexType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Companion" minOccurs="0"
maxOccurs="unbounded" type="Companion_type">
                <xs:annotation>
                    <xs:documentation>Any number of companions in any
desired pixel dimensions.</xs:documentation>
                </xs:annotation>
                </xs:element>
            </xs:sequence>
        </xs:complexType>
        </xs:element>
    <xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
        <xs:complexType>
            <xs:sequence>
                <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
                    <xs:element>
                        <xs:element name="NonLinear" minOccurs="1"
maxOccurs="unbounded" type="NonLinear_type">
                            <xs:annotation>

```

```

        <xs:documentation>Any number of companions in any
desired pixel dimensions.</xs:documentation>
        </xs:annotation>
        </xs:element>
        </xs:sequence>
        </xs:complexType>
        </xs:element>
        </xs:choice>
        <xs:attribute name="id" type="xs:string" use="optional"/>
        <xs:attribute name="sequence" type="xs:integer"
use="optional">
            <xs:annotation>
                <xs:documentation>The preferred order in which multiple
Creatives should be displayed</xs:documentation>
            </xs:annotation>
            </xs:attribute>
            <xs:attribute name="AdID" type="xs:string" use="optional">
                <xs:annotation>
                    <xs:documentation>Ad-ID for the creative (formerly ISCI)</
xs:documentation>
                </xs:annotation>
            </xs:attribute>
            </xs:complexType>
            </xs:element>
            </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="Extensions" minOccurs="0" maxOccurs="1">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Extension" type="xs:anyType" minOccurs="0"
maxOccurs="unbounded">
                        <xs:annotation>
                            <xs:documentation>Any valid XML may be included in the
Extensions node</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                    </xs:sequence>
                    </xs:complexType>
                </xs:element>
                <xs:element name="Wrapper" maxOccurs="1" minOccurs="0">
                    <xs:annotation>
                        <xs:documentation>Second-level element surrounding wrapper ad pointing to
Secondary ad server.</xs:documentation>
                    </xs:annotation>
                    <xs:complexType>
                        <xs:sequence>
                            <xs:element name="AdSystem" type="AdSystem_type" maxOccurs="1"
minOccurs="1">
                                <xs:annotation>
                                    <xs:documentation>Indicates source ad server</xs:documentation>
                                </xs:annotation>
                            </xs:element>
                            <xs:element name="VASTAdTagURI" type="xs:anyURI" maxOccurs="1"
minOccurs="1">
                                <xs:annotation>
                                    <xs:documentation>URL of ad tag of downstream Secondary Ad Server</
xs:documentation>
                                </xs:annotation>
                            </xs:element>
                            <xs:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1">
                                <xs:annotation>
                                    <xs:documentation>URL to request if ad does not play due to error</
xs:documentation>
                                </xs:annotation>
                            </xs:element>
                            <xs:element name="Impression" type="xs:anyURI" maxOccurs="unbounded"
minOccurs="1">
                                <xs:annotation>
                                    <xs:documentation>URL to request to track an impression</
xs:documentation>
                                </xs:annotation>
                            </xs:element>
                            <xs:element name="Creatives">
                                <xs:complexType>
                                    <xs:sequence>
                                        <xs:element name="Creative" maxOccurs="unbounded" minOccurs="0">
                                            <xs:complexType>
                                                <xs:choice>
                                                    <xs:element name="Linear" minOccurs="0" maxOccurs="1">

```

```

<xs:complexType>
    <xs:sequence>
        <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
            </xs:element>
        <xs:element name="VideoClicks" minOccurs="0"
maxOccurs="1">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="ClickTracking" minOccurs="0"
maxOccurs="unbounded">
                        <xs:annotation>
                            <xs:documentation>URL to request for
tracking purposes when user clicks on the video</xs:documentation>
                        </xs:annotation>
                    <xs:complexType>
                        <xs:simpleContent>
                            <xs:extension base="xs:anyURI">
                                <xs:attribute name="id" type="xs:string"
use="optional"/>
                            </xs:extension>
                        </xs:simpleContent>
                    </xs:complexType>
                </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Companion" minOccurs="0"
maxOccurs="unbounded" type="Companion_type">
                        <xs:annotation>
                            <xs:documentation>Definition of Companion ad, if
served separately</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
                        </xs:element>
                    <xs:element name="NonLinear" minOccurs="0"
maxOccurs="unbounded" type="NonLinear_type">
                        <xs:annotation>
                            <xs:documentation>Any number of companions in any
desired pixel dimensions.</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>
<xs:attribute name="id" type="xs:string" use="optional"/>
<xs:attribute name="sequence" type="xs:integer"
use="optional">
    <xs:annotation>
        <xs:documentation>The preferred order in which multiple
Creatives should be displayed</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="AdID" type="xs:string" use="optional">
    <xs:annotation>
        <xs:documentation>Ad-ID for the creative (formerly ISCI)</
xs:documentation>
    </xs:annotation>
</xs:attribute>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Extensions" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>

```

```

<xs:element name="Extension" type="xs:anyType" minOccurs="0"
maxOccurs="unbounded">
    <xs:annotation>
        <xs:documentation>Any valid XML may be included in the
Extensions node</xs:documentation>
    </xs:annotation>
    </xs:element>
    </xs:sequence>
    </xs:complexType>
    </xs:element>
    </xs:choice>
    <xs:attribute name="id" type="xs:string" use="required"/>
</xs:complexType>
</xs:element>
</xs:sequence>
<xs:attribute name="version" type="xs:string" use="required">
    <xs:annotation>
        <xs:documentation>Current version is 2.0. The 2.0.1 version corrects an error in
the Wrapper section related the Linear node's TrackingEvents and VideoClicks elements.</xs:documentation>
    </xs:annotation>
</xs:attribute>
</xs:complexType>
</xs:element>

```

Element VAST / Ad

Namespace	No namespace										
Annotations	Top-level element, wraps each ad in the response										
Diagram	<pre> classDiagram class Ad { @ id : xs:string } class InLine class Wrapper Ad "1..>" *-- "1..>" InLine Ad "1..>" *-- "1..>" Wrapper </pre>										
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: unbounded</p>										
Model	InLine{0,1} Wrapper{0,1}										
Children	InLine, Wrapper										
Instance	<Ad id=""> <InLine>{0,1}</InLine> <Wrapper>{0,1}</Wrapper> </Ad>										
Attributes	<table border="1"> <thead> <tr> <th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th></tr> </thead> <tbody> <tr> <td>id</td><td>xs:string</td><td></td><td></td><td>required</td></tr> </tbody> </table>	QName	Type	Fixed	Default	Use	id	xs:string			required
QName	Type	Fixed	Default	Use							
id	xs:string			required							
Source	<pre> <xs:element name="Ad" maxOccurs="unbounded" minOccurs="0"> <xs:annotation> <xs:documentation>Top-level element, wraps each ad in the response</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice maxOccurs="1" minOccurs="1"> <xs:element name="InLine" maxOccurs="1" minOccurs="1"> <xs:annotation> <xs:documentation>Second-level element surrounding complete ad data for a single ad</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="AdSystem" maxOccurs="1" minOccurs="1" type="AdSystem_type"> <xs:annotation> <xs:documentation>Indicates source ad server</xs:documentation> </xs:annotation> </xs:element> <xs:element name="AdTitle" type="xs:string" maxOccurs="1" minOccurs="1"> <xs:annotation> <xs:documentation>Common name of ad</xs:documentation> </pre>										

```

        </xs:annotation>
    </xs:element>
<xs:element name="Description" type="xs:string" minOccurs="0" maxOccurs="1">
    <xs:annotation>
        <xs:documentation>Longer description of ad</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="Survey" type="xs:anyURI" minOccurs="0" maxOccurs="1">
    <xs:annotation>
        <xs:documentation>URL of request to survey vendor</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1">
    <xs:annotation>
        <xs:documentation>URL to request if ad does not play due to error</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="Impression" type="Impression_type" maxOccurs="unbounded" minOccurs="1">
    <xs:annotation>
        <xs:documentation>URL to track impression</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element maxOccurs="1" minOccurs="1" name="Creatives">
    <xs:annotation>
        <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Creative" maxOccurs="unbounded">
                <xs:annotation>
                    <xs:documentation>Wraps each creative element within an InLine or Wrapper Ad</xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:choice>
                        <xs:element name="Linear" minOccurs="0" maxOccurs="1">
                            <xs:complexType>
                                <xs:sequence>
                                    <xs:element name="Duration" type="xs:time" maxOccurs="1" minOccurs="1">
                                        <xs:annotation>
                                            <xs:documentation>Duration in standard time format, hh:mm:ss</xs:documentation>
                                        </xs:annotation>
                                    </xs:element>
                                    <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1">
                                        <xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1">
                                            <xs:annotation>
                                                <xs:documentation>Data to be passed into the video ad</xs:documentation>
                                            </xs:annotation>
                                            <xs:element name="VideoClicks" minOccurs="0" type="VideoClicks_type" maxOccurs="1">
                                                <xs:element name="MediaFiles" minOccurs="0" maxOccurs="1">
                                                    <xs:complexType>
                                                        <xs:sequence>
                                                            <xs:element name="MediaFile" minOccurs="1" maxOccurs="unbounded">
                                                                <xs:annotation>
                                                                    <xs:documentation>Location of linear file</xs:documentation>
                                                                </xs:annotation>
                                                                <xs:complexType>
                                                                    <xs:simpleContent>
                                                                        <xs:extension base="xs:anyURI">
                                                                            <xs:attribute name="id" type="xs:string" use="optional">
                                                                                <xs:annotation>
                                                                                    <xs:documentation>Optional identifier</xs:documentation>
                                                                                </xs:annotation>
                                                                            </xs:attribute>
                                                                        <xs:attribute name="delivery" use="required">
                                                                            <xs:annotation>

```

```

ad</xs:documentation>
                    <xs:documentation>Method of delivery of
                </xs:annotation>
                <xs:simpleType>
                    <xs:restriction base="xs:NMTOKEN">
                        <xs:enumeration values="streaming"/>
                        <xs:enumeration value="progressive"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:attribute>
            <xs:attribute name="type" use="required"
type="xs:string">
                <xs:annotation>
                    <xs:documentation>MIME type. Popular MIME
types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/
x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles
section with appropriate Mime types</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="bitrate" type="xs:integer"
use="optional">
                <xs:annotation>
                    <xs:documentation>Bitrate of encoded video
in Kbps</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="width" type="xs:integer"
use="required">
                <xs:annotation>
                    <xs:documentation>Pixel dimensions of
video</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="height" type="xs:integer"
use="required">
                <xs:annotation>
                    <xs:documentation>Pixel dimensions of
video</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="scalable"
type="xs:boolean" use="optional">
                <xs:annotation>
                    <xs:documentation>Whether it is acceptable
to scale the image.</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="maintainAspectRatio"
type="xs:boolean" use="optional">
                <xs:annotation>
                    <xs:documentation>Whether the ad must have
its aspect ratio maintained when scales</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="apiFramework"
type="xs:string" use="optional">
                <xs:annotation>
                    <xs:documentation>The apiFramework defines
the method to use for communication if the MediaFile is interactive. Suggested values for
this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight)
and "GetVariables" (variables placed in key/value pairs on the asset request).</
xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:extension>
                </xs:simpleContent>
            </xs:complexType>
        </xs:element>
        <xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Companion" minOccurs="0"
maxOccurs="unbounded" type="Companion_type">
                        <xs:annotation>
                            <xs:documentation>Any number of companions in any
desired pixel dimensions.</xs:documentation>
                        </xs:annotation>

```

```

                </xs:element>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
        <xs:complexType>
            <xs:sequence>
                <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1">
                    </xs:element>
                    <xs:element name="NonLinear" minOccurs="1" maxOccurs="unbounded" type="NonLinear_type">
                        <xs:annotation>
                            <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                    <xs:sequence>
                        </xs:complexType>
                    </xs:element>
                </xs:choice>
                <xs:attribute name="id" type="xs:string" use="optional"/>
                <xs:attribute name="sequence" type="xs:integer" use="optional">
                    <xs:annotation>
                        <xs:documentation>The preferred order in which multiple Creatives should be displayed</xs:documentation>
                    </xs:annotation>
                </xs:attribute>
                <xs:attribute name="AdID" type="xs:string" use="optional">
                    <xs:annotation>
                        <xs:documentation>Ad-ID for the creative (formerly ISCI)</xs:documentation>
                    </xs:annotation>
                </xs:attribute>
                <xs:complexType>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="Extensions" minOccurs="0" maxOccurs="1">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Extension" type="xs:anyType" minOccurs="0" maxOccurs="unbounded">
                        <xs:annotation>
                            <xs:documentation>Any valid XML may be included in the Extensions node</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="Wrapper" maxOccurs="1" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Second-level element surrounding wrapper ad pointing to Secondary ad server.</xs:documentation>
            </xs:annotation>
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="AdSystem" type="AdSystem_type" maxOccurs="1" minOccurs="1">
                        <xs:annotation>
                            <xs:documentation>Indicates source ad server</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                    <xs:element name="VASTAdTagURI" type="xs:anyURI" maxOccurs="1" minOccurs="1">
                        <xs:annotation>
                            <xs:documentation>URL of ad tag of downstream Secondary Ad Server</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                    <xs:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1">
                        <xs:annotation>
                            <xs:documentation>URL to request if ad does not play due to error</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                    <xs:element name="Impression" type="xs:anyURI" maxOccurs="unbounded" minOccurs="1">
                        <xs:annotation>
                            <xs:documentation>URL to request to track an impression</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>

```

```

        </xs:annotation>
    </xs:element>
<xs:element name="Creatives">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Creative" maxOccurs="unbounded" minOccurs="0">
                <xs:complexType>
                    <xs:sequence>
                        <xs:element name="Linear" minOccurs="0" maxOccurs="1">
                            <xs:complexType>
                                <xs:sequence>
                                    <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
                                        <xs:element>
                                            <xs:complexType>
                                                <xs:sequence>
                                                    <xs:element name="ClickTracking" minOccurs="0"
maxOccurs="unbounded">
                                                        <xs:annotation>
                                                            <xs:documentation>URL to request for tracking
purposes when user clicks on the video</xs:documentation>
                                                        </xs:annotation>
                                                        <xs:complexType>
                                                            <xs:simpleContent>
                                                                <xs:extension base="xs:anyURI">
                                                                    <xs:attribute name="id" type="xs:string"
use="optional"/>
                                                                </xs:extension>
                                                            </xs:simpleContent>
                                                        </xs:complexType>
                                                        </xs:element>
                                                    </xs:sequence>
                                                </xs:complexType>
                                                </xs:element>
                                            </xs:sequence>
                                        </xs:complexType>
                                    </xs:element>
                                </xs:sequence>
                            </xs:complexType>
                        </xs:element>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
            <xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
                <xs:complexType>
                    <xs:sequence>
                        <xs:element name="Companion" minOccurs="0"
maxOccurs="unbounded" type="Companion_type">
                            <xs:annotation>
                                <xs:documentation>Definition of Companion ad, if served
separately</xs:documentation>
                            </xs:annotation>
                            <xs:element>
                                <xs:complexType>
                                    <xs:sequence>
                                        <xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
                                            <xs:complexType>
                                                <xs:sequence>
                                                    <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
                                                        <xs:element>
                                                            <xs:complexType>
                                                                <xs:element name="NonLinear" minOccurs="0"
maxOccurs="unbounded" type="NonLinear_type">
                                                                    <xs:annotation>
                                                                        <xs:documentation>Any number of companions in any
desired pixel dimensions.</xs:documentation>
                                                                    </xs:annotation>
                                                                </xs:element>
                                                                </xs:sequence>
                                                            </xs:complexType>
                                                        </xs:element>
                                                    </xs:sequence>
                                                </xs:complexType>
                                            </xs:element>
                                        </xs:sequence>
                                    </xs:complexType>
                                </xs:element>
                            </xs:sequence>
                        </xs:element>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
            <xs:attribute name="id" type="xs:string" use="optional"/>
            <xs:attribute name="sequence" type="xs:integer" use="optional">
                <xs:annotation>
                    <xs:documentation>The preferred order in which multiple
Creatives should be displayed</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="AdID" type="xs:string" use="optional">
                <xs:annotation>
                    <xs:documentation>Ad-ID for the creative (formerly ISCI)</
xs:documentation>
                </xs:annotation>
            </xs:attribute>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>
</xs:element>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="Extensions" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Extension" type="xs:anyType" minOccurs="0"
maxOccurs="unbounded">
                <xs:annotation>
                    <xs:documentation>Any valid XML may be included in the Extensions
node</xs:documentation>
                </xs:annotation>
            </xs:element>
        <xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:choice>
    <xs:attribute name="id" type="xs:string" use="required"/>
</xs:complexType>
</xs:element>

```

Element Ad / VAST / InLine

Namespace	No namespace						
Annotations	Second-level element surrounding complete ad data for a single ad						
Diagram	<pre> classDiagram class InLine { AdSystem "0..1" -- "1..∞" Impression AdTitle "0..1" Description "0..1" Survey "0..1" Error "0..1" Creatives "0..1" Extensions "0..1" } </pre>						
Properties	<table border="1"> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	AdSystem , AdTitle , Description{0,1} , Survey{0,1} , Error{0,1} , Impression+ , Creatives , Extensions{0,1}						
Children	AdSystem, AdTitle, Creatives, Description, Error, Extensions, Impression, Survey						
Instance	<pre> <InLine> <AdSystem version="">{1,1}</AdSystem> <AdTitle>{1,1}</AdTitle> <Description>{0,1}</Description> <Survey>{0,1}</Survey> <Error>{0,1}</Error> <Impression id="">{1,unbounded}</Impression> <Creatives>{1,1}</Creatives> <Extensions>{0,1}</Extensions> </InLine> </pre>						
Source	<pre> <xs:element name="InLine" maxOccurs="1" minOccurs="0"> <xs:annotation> <xs:documentation>Second-level element surrounding complete ad data for a single ad</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="AdSystem" maxOccurs="1" minOccurs="1" type="AdSystem_type"> <xs:annotation> <xs:documentation>Indicates source ad server</xs:documentation> </pre>						

```

        </xs:annotation>
    </xs:element>
    <xs:element name="AdTitle" type="xs:string" maxOccurs="1" minOccurs="1">
        <xs:annotation>
            <xs:documentation>Common name of ad</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="Description" type="xs:string" minOccurs="0" maxOccurs="1">
        <xs:annotation>
            <xs:documentation>Longer description of ad</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="Survey" type="xs:anyURI" minOccurs="0" maxOccurs="1">
        <xs:annotation>
            <xs:documentation>URL of request to survey vendor</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1">
        <xs:annotation>
            <xs:documentation>URL to request if ad does not play due to error</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="Impression" type="Impression_type" maxOccurs="unbounded" minOccurs="1">
        <xs:annotation>
            <xs:documentation>URL to track impression</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element maxOccurs="1" minOccurs="1" name="Creatives">
        <xs:annotation>
            <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
            <xs:sequence>
                <xs:element name="Creative" maxOccurs="unbounded">
                    <xs:annotation>
                        <xs:documentation>Wraps each creative element within an InLine or Wrapper Ad</xs:documentation>
                    </xs:annotation>
                    <xs:complexType>
                        <xs:choice>
                            <xs:element name="Linear" minOccurs="0" maxOccurs="1">
                                <xs:complexType>
                                    <xs:sequence>
                                        <xs:element name="Duration" type="xs:time" maxOccurs="1" minOccurs="1">
                                            <xs:annotation>
                                                <xs:documentation>Duration in standard time format, hh:mm:ss</xs:documentation>
                                            </xs:annotation>
                                        </xs:element>
                                    </xs:sequence>
                                </xs:complexType>
                            </xs:element>
                            <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1">
                                <xs:annotation>
                                    <xs:documentation>Data to be passed into the video ad</xs:documentation>
                                </xs:annotation>
                            </xs:element>
                            <xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1">
                                <xs:annotation>
                                    <xs:documentation>Data to be passed into the video ad</xs:documentation>
                                </xs:annotation>
                            </xs:element>
                            <xs:element name="VideoClicks" minOccurs="0" type="VideoClicks_type" maxOccurs="1">
                                <xs:annotation>
                                    <xs:documentation>Location of linear file</xs:documentation>
                                </xs:annotation>
                                <xs:complexType>
                                    <xs:simpleContent>
                                        <xs:extension base="xs:anyURI">
                                            <xs:attribute name="id" type="xs:string" use="optional">
                                                <xs:annotation>
                                                    <xs:documentation>Optional identifier</xs:documentation>
                                                </xs:annotation>
                                            </xs:attribute>
                                        </xs:extension>
                                    </xs:simpleContent>
                                </xs:complexType>
                            </xs:element>
                        </xs:choice>
                    </xs:complexType>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>
<xs:element name="MediaFiles" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="MediaFile" minOccurs="1" maxOccurs="unbounded">
                <xs:annotation>
                    <xs:documentation>Location of linear file</xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:simpleContent>
                        <xs:extension base="xs:anyURI">
                            <xs:attribute name="id" type="xs:string" use="optional">
                                <xs:annotation>
                                    <xs:documentation>Optional identifier</xs:documentation>
                                </xs:annotation>
                            </xs:attribute>
                        </xs:extension>
                    </xs:simpleContent>
                </xs:complexType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="delivery" use="required">
                <xs:annotation>
                    <xs:documentation>Method of delivery of ad</xs:documentation>
                </xs:annotation>
                <xs:simpleType>
                    <xs:restriction base="xs:NMTOKEN">
                        <xs:enumeration value="streaming"/>
                        <xs:enumeration value="progressive"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:attribute>
            <xs:attribute name="type" use="required">
                type="xs:string">
                <xs:annotation>
                    <xs:documentation>MIME type. Popular MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles section with appropriate Mime types</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="bitrate" type="xs:integer" use="optional">
                <xs:annotation>
                    <xs:documentation>Bitrate of encoded video in Kbps</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="width" type="xs:integer" use="required">
                <xs:annotation>
                    <xs:documentation>Pixel dimensions of video</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="height" type="xs:integer" use="required">
                <xs:annotation>
                    <xs:documentation>Pixel dimensions of video</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="scalable" type="xs:boolean" use="optional">
                <xs:annotation>
                    <xs:documentation>Whether it is acceptable to scale the image.</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="maintainAspectRatio" type="xs:boolean" use="optional">
                <xs:annotation>
                    <xs:documentation>Whether the ad must have its aspect ratio maintained when scales</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="apiFramework" type="xs:string" use="optional">
                <xs:annotation>
                    <xs:documentation>The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:extension>
                <xs:simpleContent>
                    <xs:complexType>
                        <xs:element>
                            <xs:sequence>
                                <xs:complexType>
                                    <xs:element>
                                        <xs:sequence>
                                            <xs:complexType>
                                                <xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
                                                    <xs:complexType>
                                                        <xs:sequence>
                                                            <xs:element name="Companion" minOccurs="0" maxOccurs="unbounded" type="Companion_type">

```

```

<xs:annotation>
    <xs:documentation>Any number of companions in any desired
pixel dimensions.</xs:documentation>
</xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
                <xs:element>
                    <xs:element name="NonLinear" minOccurs="1" maxOccurs="unbounded"
type="NonLinear_type">
                        <xs:annotation>
                            <xs:documentation>Any number of companions in any desired
pixel dimensions.</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                </xs:sequence>
                </xs:complexType>
            </xs:element>
        </xs:sequence>
        <xs:attribute name="id" type="xs:string" use="optional"/>
        <xs:attribute name="sequence" type="xs:integer" use="optional">
            <xs:annotation>
                <xs:documentation>The preferred order in which multiple Creatives
should be displayed</xs:documentation>
            </xs:annotation>
        </xs:attribute>
        <xs:attribute name="AdID" type="xs:string" use="optional">
            <xs:annotation>
                <xs:documentation>Ad-ID for the creative (formerly ISCI)</
xs:documentation>
            </xs:annotation>
        </xs:attribute>
    </xs:complexType>
    </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Extensions" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Extension" type="xs:anyType" minOccurs="0"
maxOccurs="unbounded">
                <xs:annotation>
                    <xs:documentation>Any valid XML may be included in the Extensions node</
xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

Element InLine / Ad / VAST / AdSystem

Namespace	No namespace				
Annotations	Indicates source ad server				
Diagram	<pre> classDiagram class AdSystem { <<AdSystem>> <<Type AdSystem_type>> } class AdSystem_type { <<AdSystem_type>> <<Base Type xs:string>> <<@ attributes>> <<@ version>> <<Type xs:string>> } AdSystem "1" -- "1" AdSystem_type AdSystem_type "1" -- "1" xs:string AdSystem_type "1" -- "1" attributes AdSystem_type "1" -- "1" version </pre>				
Type	AdSystem_type				
Properties	<table border="1"> <tbody> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>1</td> </tr> </tbody> </table>	content:	complex	minOccurs:	1
content:	complex				
minOccurs:	1				

	maxOccurs:	1			
Attributes	QName	Type	Fixed	Default	Use
	version	xs:string			optional
	Internal version used by ad system				

Source	<xs:element name="AdSystem" maxOccurs="1" minOccurs="1" type="AdSystem_type"> <xs:annotation> <xs:documentation>Indicates source ad server</xs:documentation> </xs:annotation> </xs:element>
--------	--

Element InLine / Ad / VAST / AdTitle

Namespace	No namespace
Annotations	Common name of ad
Diagram	
Type	xs:string
Properties	content: simple minOccurs: 1 maxOccurs: 1
Source	<xs:element name="AdTitle" type="xs:string" maxOccurs="1" minOccurs="1"> <xs:annotation> <xs:documentation>Common name of ad</xs:documentation> </xs:annotation> </xs:element>

Element InLine / Ad / VAST / Description

Namespace	No namespace
Annotations	Longer description of ad
Diagram	
Type	xs:string
Properties	content: simple minOccurs: 0 maxOccurs: 1
Source	<xs:element name="Description" type="xs:string" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>Longer description of ad</xs:documentation> </xs:annotation> </xs:element>


Element InLine / Ad / VAST / Survey

Namespace	No namespace
Annotations	URL of request to survey vendor
Diagram	
Type	xs:anyURI
Properties	content: simple minOccurs: 0 maxOccurs: 1
Source	<xs:element name="Survey" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL of request to survey vendor</xs:documentation> </xs:annotation> </xs:element>

Element InLine / Ad / VAST / Error

Namespace	No namespace
Annotations	URL to request if ad does not play due to error
Diagram	
Type	xs:anyURI
Properties	<p>content: simple</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Source	<pre><xs:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to request if ad does not play due to error</xs:documentation> </xs:annotation> </xs:element></pre>

Element InLine / Ad / VAST / Impression

Namespace	No namespace										
Annotations	URL to track impression										
Diagram											
Type	Impression_type										
Properties	<p>content: complex</p> <p>minOccurs: 1</p> <p>maxOccurs: unbounded</p>										
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>xs:string</td> <td></td> <td></td> <td>optional</td> </tr> </tbody> </table>	QName	Type	Fixed	Default	Use	id	xs:string			optional
QName	Type	Fixed	Default	Use							
id	xs:string			optional							
Source	<pre><xs:element name="Impression" type="Impression_type" maxOccurs="unbounded" minOccurs="1"> <xs:annotation> <xs:documentation>URL to track impression</xs:documentation> </xs:annotation> </xs:element></pre>										

Element InLine / Ad / VAST / Creatives

Namespace	No namespace
Annotations	Any number of companions in any desired pixel dimensions.
Diagram	
Properties	<p>content: complex</p> <p>minOccurs: 1</p> <p>maxOccurs: 1</p>
Model	Creative+
Children	Creative
Instance	<pre><Creatives> <Creative AdID="" id="" sequence="">{1,unbounded}</Creative> </Creatives></pre>
Source	<pre><xs:element maxOccurs="1" minOccurs="1" name="Creatives"> <xs:annotation> <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation> </xs:annotation></pre>

```

</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="Creative" maxOccurs="unbounded">
      <xs:annotation>
        <xs:documentation>Wraps each creative element within an InLine or Wrapper Ad</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:choice>
          <xs:element name="Linear" minOccurs="0" maxOccurs="1">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="Duration" type="xs:time" maxOccurs="1" minOccurs="1">
                  <xs:annotation>
                    <xs:documentation>Duration in standard time format, hh:mm:ss</xs:documentation>
                  </xs:annotation>
                </xs:element>
                <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1">
                  <xs:annotation>
                    <xs:documentation>Data to be passed into the video ad</xs:documentation>
                  </xs:annotation>
                </xs:element>
                <xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1">
                  <xs:annotation>
                    <xs:documentation>Data to be passed into the video ad</xs:documentation>
                  </xs:annotation>
                </xs:element>
                <xs:element name="VideoClicks" minOccurs="0" type="VideoClicks_type" maxOccurs="1">
                  <xs:annotation>
                    <xs:documentation>Method of delivery of ad</xs:documentation>
                  </xs:annotation>
                </xs:element>
                <xs:element name="MediaFiles" minOccurs="0" maxOccurs="1">
                  <xs:complexType>
                    <xs:sequence>
                      <xs:element name="MediaFile" minOccurs="1" maxOccurs="unbounded">
                        <xs:annotation>
                          <xs:documentation>Location of linear file</xs:documentation>
                        </xs:annotation>
                        <xs:complexType>
                          <xs:simpleContent>
                            <xs:extension base="xs:anyURI">
                              <xs:attribute name="id" type="xs:string" use="optional">
                                <xs:annotation>
                                  <xs:documentation>Optional identifier</xs:documentation>
                                </xs:annotation>
                              </xs:attribute>
                              <xs:attribute name="delivery" use="required">
                                <xs:annotation>
                                  <xs:documentation>Method of delivery of ad</xs:documentation>
                                </xs:annotation>
                              </xs:attribute>
                              <xs:restriction base="xs:NMTOKEN">
                                <xs:enumeration value="streaming"/>
                                <xs:enumeration value="progressive"/>
                              </xs:restriction>
                            </xs:simpleType>
                          </xs:complexType>
                          <xs:attribute name="type" use="required" type="xs:string">
                            <xs:annotation>
                              <xs:documentation>MIME type. Popular MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles section with appropriate Mime types</xs:documentation>
                            </xs:annotation>
                            <xs:attribute name="bitrate" type="xs:integer" use="optional">
                              <xs:annotation>
                                <xs:documentation>Bitrate of encoded video in Kbps</xs:documentation>
                              </xs:annotation>
                            </xs:attribute>
                            <xs:attribute name="width" type="xs:integer" use="required">
                              <xs:annotation>
                                <xs:documentation>Pixel dimensions of video</xs:documentation>
                              </xs:annotation>
                            </xs:attribute>
                          </xs:complexType>
                        </xs:element>
                      </xs:sequence>
                    </xs:complexType>
                  </xs:element>
                </xs:sequence>
              </xs:complexType>
            </xs:element>
          </xs:choice>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:annotation>

```

```

        <xs:attribute name="height" type="xs:integer"
use="required">
            <xs:annotation>
                <xs:documentation>Pixel dimensions of video</xs:documentation>
        </xs:attribute>
        <xs:attribute name="scalable" type="xs:boolean"
use="optional">
            <xs:annotation>
                <xs:documentation>Whether it is acceptable to scale
the image.</xs:documentation>
            </xs:annotation>
        </xs:attribute>
        <xs:attribute name="maintainAspectRatio" type="xs:boolean"
use="optional">
            <xs:annotation>
                <xs:documentation>Whether the ad must have its aspect
ratio maintained when scales</xs:documentation>
            </xs:annotation>
        </xs:attribute>
        <xs:attribute name="apiFramework" type="xs:string"
use="optional">
            <xs:annotation>
                <xs:documentation>The apiFramework defines the
method to use for communication if the MediaFile is interactive. Suggested values for
this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight)
and "GetVariables" (variables placed in key/value pairs on the asset request).</xs:documentation>
            </xs:annotation>
        </xs:attribute>
        </xs:extension>
        </xs:simpleContent>
    </xs:complexType>
    </xs:element>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Companion" minOccurs="0" maxOccurs="unbounded"
type="Companion_type">
                <xs:annotation>
                    <xs:documentation>Any number of companions in any desired pixel
dimensions.</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
                <xs:element name="NonLinear" minOccurs="1" maxOccurs="unbounded"
type="NonLinear_type">
                    <xs:annotation>
                        <xs:documentation>Any number of companions in any desired pixel
dimensions.</xs:documentation>
                    </xs:annotation>
                </xs:element>
            </xs:sequence>
        </xs:complexType>
</xs:element>
</xs:choice>
<xs:attribute name="id" type="xs:string" use="optional"/>
<xs:attribute name="sequence" type="xs:integer" use="optional">
    <xs:annotation>
        <xs:documentation>The preferred order in which multiple Creatives should be
displayed</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="AdID" type="xs:string" use="optional">
    <xs:annotation>
        <xs:documentation>Ad-ID for the creative (formerly ISCI)</xs:documentation>
    </xs:annotation>
</xs:attribute>

```

```

        </xs:complexType>
    </xs:element>
    </xs:sequence>
</xs:complexType>
</xs:element>

```

Element Creatives / InLine / Ad / VAST / Creative

Namespace	No namespace																														
Annotations	Wraps each creative element within an InLine or Wrapper Ad																														
Diagram	<pre> classDiagram class Creative { @id : xs:string @sequence : xs:integer @AdID : xs:string } class Linear class CompanionAds class NonLinearAds Creative "1" -- "*" Linear Creative "1" -- "*" CompanionAds Creative "1" -- "*" NonLinearAds </pre>																														
Properties	<p>content: complex</p> <p>maxOccurs: unbounded</p>																														
Model	Linear{0,1} CompanionAds{0,1} NonLinearAds{0,1}																														
Children	CompanionAds, Linear, NonLinearAds																														
Instance	<pre> <Creative AdID="" id="" sequence=""> <Linear>{0,1}</Linear> <CompanionAds>{0,1}</CompanionAds> <NonLinearAds>{0,1}</NonLinearAds> </Creative> </pre>																														
Attributes	<table border="1"> <thead> <tr> <th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th></tr> </thead> <tbody> <tr> <td>AdID</td><td>xs:string</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">Ad-ID for the creative (formerly ISCI)</td></tr> <tr> <td>id</td><td>xs:string</td><td></td><td></td><td>optional</td></tr> <tr> <td>sequence</td><td>xs:integer</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">The preferred order in which multiple Creatives should be displayed</td></tr> </tbody> </table>	QName	Type	Fixed	Default	Use	AdID	xs:string			optional		Ad-ID for the creative (formerly ISCI)				id	xs:string			optional	sequence	xs:integer			optional		The preferred order in which multiple Creatives should be displayed			
QName	Type	Fixed	Default	Use																											
AdID	xs:string			optional																											
	Ad-ID for the creative (formerly ISCI)																														
id	xs:string			optional																											
sequence	xs:integer			optional																											
	The preferred order in which multiple Creatives should be displayed																														
Source	<pre> <xs:element name="Creative" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Wraps each creative element within an InLine or Wrapper Ad</xs:documentation> <xs:annotation> <xs:complexType> <xs:choice> <xs:element name="Linear" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> <xs:element name="Duration" type="xs:time" maxOccurs="1" minOccurs="1"> <xs:annotation> <xs:documentation>Duration in standard time format, hh:mm:ss</xs:documentation> </xs:annotation> </xs:element> <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> <xs:element> <xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>Data to be passed into the video ad</xs:documentation> </xs:annotation> </xs:element> <xs:element name="VideoClicks" minOccurs="0" type="VideoClicks_type" maxOccurs="1"> <xs:element> <xs:element name="MediaFiles" minOccurs="0" maxOccurs="1"> <xs:complexType> </pre>																														

```

<xs:sequence>
  <xs:element name="MediaFile" minOccurs="1" maxOccurs="unbounded">
    <xs:annotation>
      <xs:documentation>Location of linear file</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:simpleContent>
        <xs:extension base="xs:anyURI">
          <xs:attribute name="id" type="xs:string" use="optional">
            <xs:annotation>
              <xs:documentation>Optional identifier</xs:documentation>
            </xs:annotation>
          </xs:attribute>
          <xs:attribute name="delivery" use="required">
            <xs:annotation>
              <xs:documentation>Method of delivery of ad</xs:documentation>
            </xs:annotation>
          </xs:attribute>
          <xs:simpleType>
            <xs:restriction base="xs:NMTOKEN">
              <xs:enumeration value="streaming"/>
              <xs:enumeration value="progressive"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:extension>
      </xs:simpleContent>
      <xs:attribute name="type" use="required" type="xs:string">
        <xs:annotation>
          <xs:documentation>MIME type. Popular MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles section with appropriate Mime types</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="bitrate" type="xs:integer" use="optional">
        <xs:annotation>
          <xs:documentation>Bitrate of encoded video in Kbps</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="width" type="xs:integer" use="required">
        <xs:annotation>
          <xs:documentation>Pixel dimensions of video</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="height" type="xs:integer" use="required">
        <xs:annotation>
          <xs:documentation>Pixel dimensions of video</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="scalable" type="xs:boolean" use="optional">
        <xs:annotation>
          <xs:documentation>Whether it is acceptable to scale the image.</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="maintainAspectRatio" type="xs:boolean" use="optional">
        <xs:annotation>
          <xs:documentation>Whether the ad must have its aspect ratio maintained when scales</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="apiFramework" type="xs:string" use="optional">
        <xs:annotation>
          <xs:documentation>The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension>
            <xs:attribute>
              <xs:annotation>
                <xs:documentation>The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).</xs:documentation>
              </xs:annotation>
            </xs:attribute>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>

```

```

</xs:element>
<xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Companion" minOccurs="0" maxOccurs="unbounded"
type="Companion_type">
                <xs:annotation>
                    <xs:documentation>Any number of companions in any desired pixel
dimensions.</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
<xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type"
maxOccurs="1">
                <xs:annotation>
                    <xs:documentation>Any number of companions in any desired pixel
dimensions.</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="NonLinear" minOccurs="1" maxOccurs="unbounded"
type="NonLinear_type">
                <xs:annotation>
                    <xs:documentation>Any number of companions in any desired pixel
dimensions.</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:choice>
    <xs:attribute name="id" type="xs:string" use="optional"/>
    <xs:attribute name="sequence" type="xs:integer" use="optional">
        <xs:annotation>
            <xs:documentation>The preferred order in which multiple Creatives should be
displayed</xs:documentation>
        </xs:annotation>
    </xs:attribute>
    <xs:attribute name="AdID" type="xs:string" use="optional">
        <xs:annotation>
            <xs:documentation>Ad-ID for the creative (formerly ISCI)</xs:documentation>
        </xs:annotation>
    </xs:attribute>
</xs:choice>
</xs:complexType>
</xs:element>

```

Element Creative / Creatives / InLine / Ad / VAST / Linear

Namespace	No namespace
Diagram	<pre> classDiagram class Linear { <<Duration>> <<TrackingEvents>> <<AdParameters>> <<VideoClicks>> <<MediaFiles>> } Linear < --> Linear Duration < --> Linear TrackingEvents < --> Linear AdParameters < --> Linear VideoClicks < --> Linear MediaFiles < --> Linear </pre>
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Model	Duration , TrackingEvents{0,1} , AdParameters{0,1} , VideoClicks{0,1} , MediaFiles{0,1}
Children	AdParameters, Duration, MediaFiles, TrackingEvents, VideoClicks
Instance	<pre> <Linear> <Duration>{1,1}</Duration> <TrackingEvents>{0,1}</TrackingEvents> <AdParameters>{0,1}</AdParameters> <VideoClicks>{0,1}</VideoClicks> <MediaFiles>{0,1}</MediaFiles> </Linear> </pre>
Source	<xs:element name="Linear" minOccurs="0" maxOccurs="1">

```

<xs:complexType>
  <xs:sequence>
    <xs:element name="Duration" type="xs:time" maxOccurs="1" minOccurs="1">
      <xs:annotation>
        <xs:documentation>Duration in standard time format, hh:mm:ss</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type"
maxOccurs="1">
    </xs:element>
    <xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1">
      <xs:annotation>
        <xs:documentation>Data to be passed into the video ad</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="VideoClicks" minOccurs="0" type="VideoClicks_type" maxOccurs="1">
    </xs:element>
    <xs:element name="MediaFiles" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="MediaFile" minOccurs="1" maxOccurs="unbounded">
            <xs:annotation>
              <xs:documentation>Location of linear file</xs:documentation>
            </xs:annotation>
            <xs:complexType>
              <xs:simpleContent>
                <xs:extension base="xs:anyURI">
                  <xs:attribute name="id" type="xs:string" use="optional">
                    <xs:annotation>
                      <xs:documentation>Optional identifier</xs:documentation>
                    </xs:annotation>
                  </xs:attribute>
                  <xs:attribute name="delivery" use="required">
                    <xs:annotation>
                      <xs:documentation>Method of delivery of ad</xs:documentation>
                    </xs:annotation>
                  </xs:attribute>
                  <xs:attribute name="type" use="required" type="xs:string">
                    <xs:annotation>
                      <xs:documentation>MIME type. Popular MIME types include, but are
not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video.
Image ads or interactive ads can be included in the MediaFiles section with appropriate
Mime types</xs:documentation>
                    </xs:annotation>
                  </xs:attribute>
                  <xs:attribute name="bitrate" type="xs:integer" use="optional">
                    <xs:annotation>
                      <xs:documentation>Bitrate of encoded video in Kbps</
xs:documentation>
                    </xs:annotation>
                  </xs:attribute>
                  <xs:attribute name="width" type="xs:integer" use="required">
                    <xs:annotation>
                      <xs:documentation>Pixel dimensions of video</xs:documentation>
                    </xs:annotation>
                  </xs:attribute>
                  <xs:attribute name="height" type="xs:integer" use="required">
                    <xs:annotation>
                      <xs:documentation>Pixel dimensions of video</xs:documentation>
                    </xs:annotation>
                  </xs:attribute>
                  <xs:attribute name="scalable" type="xs:boolean" use="optional">
                    <xs:annotation>
                      <xs:documentation>Whether it is acceptable to scale the image.</
xs:documentation>
                    </xs:annotation>
                  </xs:attribute>
                  <xs:attribute name="maintainAspectRatio" type="xs:boolean"
use="optional">
                    <xs:annotation>
                      <xs:documentation>Whether the ad must have its aspect ratio
maintained when scales</xs:documentation>
                    </xs:annotation>
                  </xs:attribute>
                  <xs:attribute name="apiFramework" type="xs:string" use="optional">
                    <xs:annotation>

```

```


<xs:documentation>The apiFramework defines the method to
use for communication if the MediaFile is interactive. Suggested values for this
element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight)
and "GetVariables" (variables placed in key/value pairs on the asset request).</
xs:documentation>
    </xs:annotation>
</xs:attribute>
</xs:extension>
</xs:simpleContent>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```


Element Linear / Creative / Creatives / InLine / Ad / VAST / Duration

Namespace	No namespace						
Annotations	Duration in standard time format, hh:mm:ss						
Diagram							
Type	xs:time						
Properties	<table border="1"> <tr> <td>content:</td> <td>simple</td> </tr> <tr> <td>minOccurs:</td> <td>1</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	simple	minOccurs:	1	maxOccurs:	1
content:	simple						
minOccurs:	1						
maxOccurs:	1						
Source	<xs:element name="Duration" type="xs:time" maxOccurs="1" minOccurs="1"> <xs:annotation> <xs:documentation>Duration in standard time format, hh:mm:ss</xs:documentation> </xs:annotation> </xs:element>						

Element Linear / Creative / Creatives / InLine / Ad / VAST / TrackingEvents

Namespace	No namespace						
Diagram							
Type	TrackingEvents_type						
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	Tracking*						
Children	Tracking						
Instance	<TrackingEvents> <Tracking event="">{0,unbounded}</Tracking> </TrackingEvents>						
Source	<xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xs:element>						

Element TrackingEvents_type / Tracking

Namespace	No namespace
Annotations	The name of the event to track for the Linear element. The creativeView should always be requested when present.
Diagram	


Type	extension of xs:anyURI																		
Properties	content: complex minOccurs: 0 maxOccurs: unbounded																		
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>event</td> <td>restriction of xs:NMTOKEN</td> <td></td> <td></td> <td>required</td> </tr> <tr> <td></td> <td colspan="4">The name of the event to track. For nonlinear ads these events should be recorded on the video within the ad.</td></tr> </tbody> </table>				QName	Type	Fixed	Default	Use	event	restriction of xs:NMTOKEN			required		The name of the event to track. For nonlinear ads these events should be recorded on the video within the ad.			
QName	Type	Fixed	Default	Use															
event	restriction of xs:NMTOKEN			required															
	The name of the event to track. For nonlinear ads these events should be recorded on the video within the ad.																		
Source	<pre> <xs:element name="Tracking" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>The name of the event to track for the Linear element. The creativeView should always be requested when present.</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="event" use="required"> <xs:annotation> <xs:documentation>The name of the event to track. For nonlinear ads these events should be recorded on the video within the ad.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="creativeView"/> <xs:enumeration value="start"/> <xs:enumeration value="midpoint"/> <xs:enumeration value="firstQuartile"/> <xs:enumeration value="thirdQuartile"/> <xs:enumeration value="complete"/> <xs:enumeration value="mute"/> <xs:enumeration value="unmute"/> <xs:enumeration value="pause"/> <xs:enumeration value="rewind"/> <xs:enumeration value="resume"/> <xs:enumeration value="fullscreen"/> <xs:enumeration value="expand"/> <xs:enumeration value="collapse"/> <xs:enumeration value="acceptInvitation"/> <xs:enumeration value="close"/> </xs:restriction> </xs:simpleType> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>																		

Element Linear / Creative / Creatives / InLine / Ad / VAST / AdParameters


Namespace	No namespace	
Annotations	Data to be passed into the video ad	
Diagram	<pre> classDiagram class AdParameters { type xs:string } xs:string AdParameters "1" -- "0..1" xs:string </pre>	
Type	xs:string	
Properties	content: simple minOccurs: 0 maxOccurs: 1	
Source	<pre> <xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>Data to be passed into the video ad</xs:documentation> </xs:annotation> </xs:element> </pre>	

Element Linear / Creative / Creatives / InLine / Ad / VAST / VideoClicks

Namespace	No namespace
-----------	--------------


Diagram	
Type	VideoClicks_type
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Model	ClickThrough{0,1} , ClickTracking* , CustomClick*
Children	ClickThrough, ClickTracking, CustomClick
Instance	<pre><VideoClicks> <ClickThrough id="">{0,1}</ClickThrough> <ClickTracking id="">{0,unbounded}</ClickTracking> <CustomClick id="">{0,unbounded}</CustomClick> </VideoClicks></pre>
Source	<pre><xs:element name="VideoClicks" minOccurs="0" type="VideoClicks_type" maxOccurs="1"> </xs:element></pre>

Element VideoClicks_type / ClickThrough


Namespace	No namespace										
Annotations	URL to open as destination page when user clicks on the video										
Diagram											
Type	extension of xs:anyURI										
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>										
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>xs:string</td> <td></td> <td></td> <td>optional</td> </tr> </tbody> </table>	QName	Type	Fixed	Default	Use	id	xs:string			optional
QName	Type	Fixed	Default	Use							
id	xs:string			optional							
Source	<pre><xs:element name="ClickThrough" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to open as destination page when user clicks on the video</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>										

Element VideoClicks_type / ClickTracking


Namespace	No namespace
Annotations	URL to request for tracking purposes when user clicks on the video

Diagram											
Type	extension of xs:anyURI										
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>unbounded</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	unbounded				
content:	complex										
minOccurs:	0										
maxOccurs:	unbounded										
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>xs:string</td> <td></td> <td></td> <td>optional</td> </tr> </tbody> </table>	QName	Type	Fixed	Default	Use	id	xs:string			optional
QName	Type	Fixed	Default	Use							
id	xs:string			optional							
Source	<pre><xs:element name="ClickTracking" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>URL to request for tracking purposes when user clicks on the video</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>										

Element VideoClicks_type / CustomClick

Namespace	No namespace										
Annotations	URLs to request on custom events such as hotspotted video										
Diagram											
Type	extension of xs:anyURI										
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>unbounded</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	unbounded				
content:	complex										
minOccurs:	0										
maxOccurs:	unbounded										
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>xs:string</td> <td></td> <td></td> <td>optional</td> </tr> </tbody> </table>	QName	Type	Fixed	Default	Use	id	xs:string			optional
QName	Type	Fixed	Default	Use							
id	xs:string			optional							
Source	<pre><xs:element name="CustomClick" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>URLs to request on custom events such as hotspotted video</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>										

Element Linear / Creative / Creatives / InLine / Ad / VAST / MediaFiles

Namespace	No namespace
Diagram	
Properties	content: complex

	minOccurs: 0 maxOccurs: 1
Model	MediaFile+
Children	MediaFile
Instance	<MediaFiles> <MediaFile apiFramework="" bitrate="" delivery="" height="" id="" maintainAspectRatio="" scalable="" t MediaFile> </MediaFiles>
Source	<xs:element name="MediaFiles" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> <xs:element name="MediaFile" minOccurs="1" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Location of linear file</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Optional identifier</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="delivery" use="required"> <xs:annotation> <xs:documentation>Method of delivery of ad</xs:documentation> </xs:annotation> <xs:attribute> <xs:annotation> <xs:documentation>MIME type. Popular MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles section with appropriate Mime types</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="bitrate" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>Bitrate of encoded video in Kbps</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="width" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of video</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="height" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of video</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="scalable" type="xs:boolean" use="optional"> <xs:annotation> <xs:documentation>Whether it is acceptable to scale the image.</xs: documentation> </xs:annotation> </xs:attribute> <xs:attribute name="maintainAspectRatio" type="xs:boolean" use="optional"> <xs:annotation> <xs:documentation>Whether the ad must have its aspect ratio maintained when scales</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="apiFramework" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).</xs: documentation> </xs:annotation> </xs:attribute> </xs:extension>

```

        </xs:simpleContent>
    </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

Element MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / MediaFile

Namespace	No namespace																																																																						
Annotations	Location of linear file																																																																						
Diagram	<pre> classDiagram class MediaFile { <<extension of xs:anyURI>> } xs:anyURI "1.." MediaFile "1.." MediaFile { @id : xs:string @delivery : restriction of xs:NMTOKEN @type : xs:string @bitrate : xs:integer @width : xs:integer @height : xs:integer @scalable : xs:boolean @maintainAspectRatio : xs:boolean @apiFramework : xs:string } </pre>																																																																						
Type	extension of xs:anyURI																																																																						
Properties	<p>content: complex</p> <p>minOccurs: 1</p> <p>maxOccurs: unbounded</p>																																																																						
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>apiFramework</td> <td>xs:string</td> <td></td> <td></td> <td>optional</td> </tr> <tr> <td></td> <td colspan="4"> The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request). </td></tr> <tr> <td>bitrate</td> <td>xs:integer</td> <td></td> <td></td> <td>optional</td> </tr> <tr> <td></td> <td colspan="4">Bitrate of encoded video in Kbps</td></tr> <tr> <td>delivery</td> <td>restriction of xs:NMTOKEN</td> <td></td> <td></td> <td>required</td> </tr> <tr> <td></td> <td colspan="4">Method of delivery of ad</td></tr> <tr> <td>height</td> <td>xs:integer</td> <td></td> <td></td> <td>required</td> </tr> <tr> <td></td> <td colspan="4">Pixel dimensions of video</td></tr> <tr> <td>id</td> <td>xs:string</td> <td></td> <td></td> <td>optional</td> </tr> <tr> <td></td> <td colspan="4">Optional identifier</td></tr> <tr> <td>maintainAspectRatio</td> <td>xs:boolean</td> <td></td> <td></td> <td>optional</td> </tr> <tr> <td></td> <td colspan="4">Whether the ad must have its aspect ratio maintained when scales</td></tr> <tr> <td>scalable</td> <td>xs:boolean</td> <td></td> <td></td> <td>optional</td> </tr> </tbody> </table>	QName	Type	Fixed	Default	Use	apiFramework	xs:string			optional		The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).				bitrate	xs:integer			optional		Bitrate of encoded video in Kbps				delivery	restriction of xs:NMTOKEN			required		Method of delivery of ad				height	xs:integer			required		Pixel dimensions of video				id	xs:string			optional		Optional identifier				maintainAspectRatio	xs:boolean			optional		Whether the ad must have its aspect ratio maintained when scales				scalable	xs:boolean			optional
QName	Type	Fixed	Default	Use																																																																			
apiFramework	xs:string			optional																																																																			
	The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).																																																																						
bitrate	xs:integer			optional																																																																			
	Bitrate of encoded video in Kbps																																																																						
delivery	restriction of xs:NMTOKEN			required																																																																			
	Method of delivery of ad																																																																						
height	xs:integer			required																																																																			
	Pixel dimensions of video																																																																						
id	xs:string			optional																																																																			
	Optional identifier																																																																						
maintainAspectRatio	xs:boolean			optional																																																																			
	Whether the ad must have its aspect ratio maintained when scales																																																																						
scalable	xs:boolean			optional																																																																			

	QName	Type	Fixed	Default	Use
		Whether it is acceptable to scale the image.			
	type	xs:string			required
		MIME type. Popular MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles section with appropriate Mime types			
	width	xs:integer			required
		Pixel dimensions of video			
Source	<pre> <xs:element name="MediaFile" minOccurs="1" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Location of linear file</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Optional identifier</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="delivery" use="required"> <xs:annotation> <xs:documentation>Method of delivery of ad</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="streaming"/> <xs:enumeration value="progressive"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="type" use="required" type="xs:string"> <xs:annotation> <xs:documentation>MIME type. Popular MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles section with appropriate Mime types</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="bitrate" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>Bitrate of encoded video in Kbps</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="width" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of video</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="height" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of video</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="scalable" type="xs:boolean" use="optional"> <xs:annotation> <xs:documentation>Whether it is acceptable to scale the image.</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="maintainAspectRatio" type="xs:boolean" use="optional"> <xs:annotation> <xs:documentation>Whether the ad must have its aspect ratio maintained when scales</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="apiFramework" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).</xs:documentation> </xs:annotation> </xs:attribute> </xs:simpleContent> </xs:complexType> </xs:element></pre>				

```

    </xs:complexType>
</xs:element>

```


Element Creative / Creatives / InLine / Ad / VAST / CompanionAds

Namespace	No namespace
Diagram	<pre> classDiagram class CompanionAds class Companion_Type CompanionAds "0..∞" --> "0..∞" Companion_Type </pre>
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Model	Companion*
Children	Companion
Instance	<pre> <CompanionAds> <Companion apiFramework="" expandedHeight="" expandedWidth="" height="" id="" width="">{0,unbounded}</Companion> </CompanionAds> </pre>
Source	<pre> <xs:element name="CompanionAds" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> <xs:element name="Companion" minOccurs="0" maxOccurs="unbounded" type="Companion_type"> <xs:annotation> <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

Element CompanionAds / Creative / Creatives / InLine / Ad / VAST / Companion

Namespace	No namespace
Annotations	Any number of companions in any desired pixel dimensions.

Diagram



Type	Companion_type
------	----------------

Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: unbounded</p>
------------	---

Model	(StaticResource{0,1} IFrameResource{0,1} HTMLResource{0,1}) , TrackingEvents{0,1} , CompanionClickThrough{0,1} , AltText{0,1} , AdParameters{0,1}
-------	---

Children	AdParameters, AltText, CompanionClickThrough, HTMLResource, IFrameResource, StaticResource, TrackingEvents
----------	--

Instance	<Companion apiFramework="" expandedHeight="" expandedWidth="" height="" id="" width=""> <StaticResource creativeType="">{0,1}</StaticResource> <IFrameResource>{0,1}</IFrameResource> <HTMLResource>{0,1}</HTMLResource> <TrackingEvents>{0,1}</TrackingEvents> <CompanionClickThrough>{0,1}</CompanionClickThrough> <AltText>{0,1}</AltText> <AdParameters>{0,1}</AdParameters> </Companion>
----------	---

Attributes	QName	Type	Fixed	Default	Use
	apiFramework	xs:string			optional
	The apiFramework defines the method to use for communication with the companion				
	expandedHeight	xs:integer			optional
	Pixel dimensions of expanding companion ad when in expanded state				
	expandedWidth	xs:integer			optional
	Pixel dimensions of expanding companion ad when in expanded state				
	height	xs:integer			required

	QName	Type	Fixed	Default	Use
Pixel dimensions of companion					
id	xs:string				optional
Optional identifier					
width	xs:integer				required
Pixel dimensions of companion					
Source	<pre><xs:element name="Companion" minOccurs="0" maxOccurs="unbounded" type="Companion_type"> <xs:annotation> <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation> </xs:annotation> </xs:element></pre>				

Element Companion_type / StaticResource

Namespace	No namespace										
Annotations	URL to a static file, such as an image or SWF file										
Diagram	<pre> classDiagram class StaticResource { <<extension of xs:anyURI>> attribute @creativeType xs:string } xs:anyURI "xs:anyURI" @creativeType "creativeType" </pre>										
Type	extension of xs:anyURI										
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>					content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex										
minOccurs:	0										
maxOccurs:	1										
Attributes	QName	Type	Fixed	Default	Use						
	creativeType	xs:string			required						
Mime type of static resource											
Source	<pre><xs:element name="StaticResource" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to a static file, such as an image or SWF file</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="creativeType" type="xs:string" use="required"> <xs:annotation> <xs:documentation>Mime type of static resource</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>										

Element Companion_type / IFrameResource

Namespace	No namespace										
Annotations	URL source for an IFrame to display the companion element										
Diagram	<pre> classDiagram class IFrameResource { <<xs:anyURI>> } xs:anyURI "xs:anyURI" </pre>										
Type	xs:anyURI										
Properties	<table border="1"> <tr> <td>content:</td> <td>simple</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>					content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple										
minOccurs:	0										
maxOccurs:	1										
Source	<pre><xs:element name="IFrameResource" type="xs:anyURI" minOccurs="0" maxOccurs="1"></pre>										

```


<xs:annotation>
  <xs:documentation>URL source for an IFrame to display the companion element</
  xs:documentation>
</xs:annotation>
</xs:element>

```


Element Companion_type / HTMLResource

Namespace	No namespace						
Annotations	HTML to display the companion element						
Diagram							
Type	xs:string						
Properties	<table> <tr> <td>content:</td> <td>simple</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Source	<xs:element name="HTMLResource" type="xs:string" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>HTML to display the companion element</xs:documentation> </xs:annotation> </xs:element>						

Element Companion_type / TrackingEvents

Namespace	No namespace						
Annotations	The creativeView should always be requested when present. For Companions creativeView is the only supported event.						
Diagram							
Type	TrackingEvents_type						
Properties	<table> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	Tracking*						
Children	Tracking						
Instance	<TrackingEvents> <Tracking event="">{0,unbounded}</Tracking> </TrackingEvents>						
Source	<xs:element maxOccurs="1" minOccurs="0" name="TrackingEvents" type="TrackingEvents_type"> <xs:annotation> <xs:documentation>The creativeView should always be requested when present. For Companions creativeView is the only supported event.</xs:documentation> </xs:annotation> </xs:element>						

Element Companion_type / CompanionClickThrough

Namespace	No namespace						
Annotations	URL to open as destination page when user clicks on the the companion banner ad.						
Diagram							
Type	xs:anyURI						
Properties	<table> <tr> <td>content:</td> <td>simple</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						

Source	<pre><xss:element name="CompanionClickThrough" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>URL to open as destination page when user clicks on the the companion banner ad.</xss:documentation> </xss:annotation> </xss:element></pre>
--------	--

Element Companion_type / AltText

Namespace	No namespace						
Annotations	Alt text to be displayed when companion is rendered in HTML environment.						
Diagram							
Type	xs:string						
Properties	<table border="1"> <tr> <td>content:</td> <td>simple</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Source	<pre><xss:element name="AltText" type="xs:string" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>Alt text to be displayed when companion is rendered in HTML environment.</xss:documentation> </xss:annotation> </xss:element></pre>						

Element Companion_type / AdParameters

Namespace	No namespace						
Annotations	Data to be passed into the companion ads. The apiFramework defines the method to use for communication (e.g. "FlashVar")						
Diagram							
Type	xs:string						
Properties	<table border="1"> <tr> <td>content:</td> <td>simple</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Source	<pre><xss:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>Data to be passed into the companion ads. The apiFramework defines the method to use for communication (e.g. "FlashVar")</xss:documentation> </xss:annotation> </xss:element></pre>						

Element Creative / Creatives / InLine / Ad / VAST / NonLinearAds

Namespace	No namespace						
Diagram							
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	TrackingEvents{0,1} , NonLinear+						
Children	NonLinear, TrackingEvents						
Instance	<pre><NonLinearAds> <TrackingEvents>{0,1}</TrackingEvents> <NonLinear apiFramework="" expandedHeight="" expandedWidth="" height="" id="" maintainAspectRatio="" NonLinear></pre>						

	</NonLinearAds>
Source	<pre> <xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xs:element> <xs:element name="NonLinear" minOccurs="1" maxOccurs="unbounded" type="NonLinear_type"> <xs:annotation> <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>


Element NonLinearAds / Creative / Creatives / InLine / Ad / VAST / TrackingEvents

Namespace	No namespace						
Diagram	<pre> classDiagram class TrackingEvents { <<TrackingEvents_type>> } class Tracking { <<extension of 'xs:anyURI'>> } TrackingEvents < -- Tracking </pre>						
Type	TrackingEvents_type						
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	Tracking*						
Children	Tracking						
Instance	<pre> <TrackingEvents> <Tracking event="">{0,unbounded}</Tracking> </TrackingEvents> </pre>						
Source	<pre> <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xs:element> </pre>						

Element NonLinearAds / Creative / Creatives / InLine / Ad / VAST / NonLinear

Namespace	No namespace
Annotations	Any number of companions in any desired pixel dimensions.

Diagram



Type	NonLinear_type																																								
Properties	<p>content: complex</p> <p>minOccurs: 1</p> <p>maxOccurs: unbounded</p>																																								
Model	(<code>StaticResource{0,1}</code> <code>IFrameResource{0,1}</code> <code>HTMLResource{0,1}</code>) , <code>NonLinearClickThrough{0,1}</code> , <code>AdParameters{0,1}</code>																																								
Children	AdParameters, HTMLResource, IFrameResource, NonLinearClickThrough, StaticResource																																								
Instance	<pre><NonLinear apiFramework="" expandedHeight="" expandedWidth="" height="" id="" maintainAspectRatio="" minSuggestedDuration=""> <StaticResource creativeType="">{0,1}</StaticResource> <IFrameResource>{0,1}</IFrameResource> <HTMLResource>{0,1}</HTMLResource> <NonLinearClickThrough>{0,1}</NonLinearClickThrough> <AdParameters>{0,1}</AdParameters> </NonLinear></pre>																																								
Attributes	<table border="1"> <thead> <tr> <th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th></tr> </thead> <tbody> <tr> <td>apiFramework</td><td>xs:string</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">The <code>apiFramework</code> defines the method to use for communication with the nonlinear element</td></tr> <tr> <td>expandedHeight</td><td>xs:integer</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">Pixel dimensions of expanding nonlinear ad when in expanded state</td></tr> <tr> <td>expandedWidth</td><td>xs:integer</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">Pixel dimensions of expanding nonlinear ad when in expanded state</td></tr> <tr> <td>height</td><td>xs:integer</td><td></td><td></td><td>required</td></tr> </tbody> </table>	QName	Type	Fixed	Default	Use	apiFramework	xs:string			optional		The <code>apiFramework</code> defines the method to use for communication with the nonlinear element				expandedHeight	xs:integer			optional		Pixel dimensions of expanding nonlinear ad when in expanded state				expandedWidth	xs:integer			optional		Pixel dimensions of expanding nonlinear ad when in expanded state				height	xs:integer			required
QName	Type	Fixed	Default	Use																																					
apiFramework	xs:string			optional																																					
	The <code>apiFramework</code> defines the method to use for communication with the nonlinear element																																								
expandedHeight	xs:integer			optional																																					
	Pixel dimensions of expanding nonlinear ad when in expanded state																																								
expandedWidth	xs:integer			optional																																					
	Pixel dimensions of expanding nonlinear ad when in expanded state																																								
height	xs:integer			required																																					

	QName	Type	Fixed	Default	Use
		Pixel dimensions of companion			
	id	xs:string			optional
		Optional identifier			
	maintainAspectRatio	xs:boolean			optional
		Whether the ad must have its aspect ratio maintained when scales			
	minSuggestedDuration	xs:time			optional
		Suggested duration to display non-linear ad, typically for animation to complete. Expressed in standard time format hh:mm:ss			
	scalable	xs:boolean			optional
		Whether it is acceptable to scale the image.			
	width	xs:integer			required
		Pixel dimensions of companion			
Source	<xs:element name="NonLinear" minOccurs="1" maxOccurs="unbounded" type="NonLinear_type"> <xs:annotation> <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation> </xs:annotation> </xs:element>				

Element NonLinear_type / StaticResource


Namespace	No namespace																			
Annotations	URL to a static file, such as an image or SWF file																			
Diagram	<pre> classDiagram class StaticResource { <<extension of xs:anyURI>> <<@ attributes>> <<@ creativeType xs:string>> } </pre>																			
Type	extension of xs:anyURI																			
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>					content:	complex	minOccurs:	0	maxOccurs:	1									
content:	complex																			
minOccurs:	0																			
maxOccurs:	1																			
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>creativeType</td> <td>xs:string</td> <td></td> <td></td> <td>required</td> </tr> <tr> <td></td> <td colspan="4">Mime type of static resource</td></tr> </tbody> </table>	QName	Type	Fixed	Default	Use	creativeType	xs:string			required		Mime type of static resource							
QName	Type	Fixed	Default	Use																
creativeType	xs:string			required																
	Mime type of static resource																			
Source	<xs:element name="StaticResource" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to a static file, such as an image or SWF file</xs:documentation> </xs:annotation> </xs:element>																			

Element NonLinear_type / IFrameResource


Namespace	No namespace				
Annotations	URL source for an IFrame to display the companion element				
Diagram	<pre> classDiagram class IFrameResource { <<xs:anyURI>> } </pre>				

Type	xs:anyURI
Properties	<p>content: simple</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Source	<pre><xs:element name="IFrameResource" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL source for an IFrame to display the companion element</xs:documentation> </xs:annotation> </xs:element></pre>


Element NonLinear_type / HTMLResource

Namespace	No namespace
Annotations	HTML to display the companion element
Diagram	
Type	xs:string
Properties	<p>content: simple</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Source	<pre><xs:element name="HTMLResource" type="xs:string" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>HTML to display the companion element</xs:documentation> </xs:annotation> </xs:element></pre>

Element NonLinear_type / NonLinearClickThrough

Namespace	No namespace
Annotations	URL to open as destination page when user clicks on the non-linear ad unit.
Diagram	
Type	xs:anyURI
Properties	<p>content: simple</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Source	<pre><xs:element name="NonLinearClickThrough" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to open as destination page when user clicks on the non-linear ad unit.</xs:documentation> </xs:annotation> </xs:element></pre>

Element NonLinear_type / AdParameters

Namespace	No namespace
Annotations	Data to be passed into the video ad.
Diagram	
Type	xs:string
Properties	<p>content: simple</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Source	<pre><xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>Data to be passed into the video ad.</xs:documentation> </xs:annotation> </xs:element></pre>

Element InLine / Ad / VAST / Extensions

Namespace	No namespace
Diagram	
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Model	Extension*
Children	Extension
Instance	<Extensions> <Extension>{0,unbounded}</Extension> </Extensions>
Source	<pre><xss:element name="Extensions" minOccurs="0" maxOccurs="1"> <xss:complexType> <xss:sequence> <xss:element name="Extension" type="xss:anyType" minOccurs="0" maxOccurs="unbounded"> <xss:annotation> <xss:documentation>Any valid XML may be included in the Extensions node</xss:documentation> </xss:annotation> </xss:element> </xss:sequence> </xss:complexType> </xss:element></pre>

Element Extensions / InLine / Ad / VAST / Extension

Namespace	No namespace
Annotations	Any valid XML may be included in the Extensions node
Diagram	
Properties	<p>minOccurs: 0</p> <p>maxOccurs: unbounded</p>
Source	<pre><xss:element name="Extension" type="xss:anyType" minOccurs="0" maxOccurs="unbounded"> <xss:annotation> <xss:documentation>Any valid XML may be included in the Extensions node</xss:documentation> </xss:annotation> </xss:element></pre>

Element Ad / VAST / Wrapper

Namespace	No namespace
Annotations	Second-level element surrounding wrapper ad pointing to Secondary ad server.
Diagram	

Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Model	AdSystem , VASTAdTagURI , Error{0,1} , Impression+ , Creatives , Extensions{0,1}
Children	AdSystem, Creatives, Error, Extensions, Impression, VASTAdTagURI
Instance	<pre><Wrapper> <AdSystem version="">{1,1}</AdSystem> <VASTAdTagURI>{1,1}</VASTAdTagURI> <Error>{0,1}</Error> <Impression>{1,unbounded}</Impression> <Creatives>{1,1}</Creatives> <Extensions>{0,1}</Extensions> </Wrapper></pre>
Source	<pre><xss:element name="Wrapper" maxOccurs="1" minOccurs="0"> <xss:annotation> <xss:documentation>Second-level element surrounding wrapper ad pointing to Secondary ad server.</xss:documentation> </xss:annotation> <xss:complexType> <xss:sequence> <xss:element name="AdSystem" type="AdSystem_type" maxOccurs="1" minOccurs="1"> <xss:annotation> <xss:documentation>Indicates source ad server</xss:documentation> </xss:annotation> </xss:element> <xss:element name="VASTAdTagURI" type="xs:anyURI" maxOccurs="1" minOccurs="1"> <xss:annotation> <xss:documentation>URL of ad tag of downstream Secondary Ad Server</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xss:annotation> <xss:documentation>URL to request if ad does not play due to error</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Impression" type="xs:anyURI" maxOccurs="unbounded" minOccurs="1"> <xss:annotation> <xss:documentation>URL to request to track an impression</xss:documentation> </xss:annotation> </xss:element> <xss:element name="Creatives"> <xss:complexType> <xss:sequence> <xss:element name="Creative" maxOccurs="unbounded" minOccurs="0"> <xss:complexType> <xss:choice> <xss:element name="Linear" minOccurs="0" maxOccurs="1"> <xss:complexType> <xss:sequence> <xss:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xss:element> <xss:element name="VideoClicks" minOccurs="0" maxOccurs="1"> <xss:complexType> <xss:sequence> <xss:element name="ClickTracking" minOccurs="0" maxOccurs="unbounded"> <xss:annotation> <xss:documentation>URL to request for tracking purposes when user clicks on the video</xss:documentation> </xss:annotation> <xss:complexType> <xss:simpleContent> <xss:extension base="xs:anyURI"> <xss:attribute name="id" type="xs:string" use="optional"/> </xss:extension> </xss:simpleContent> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:choice> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:element> </xss:element></pre>

```

<xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Companion" minOccurs="0" maxOccurs="unbounded"
type="Companion_type">
                <xs:annotation>
                    <xs:documentation>Definition of Companion ad, if served
separately</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="TrackingEvents" minOccurs="0"
type="TrackingEvents_type" maxOccurs="1">
                <xs:element>
                    <xs:complexType>
                        <xs:sequence>
                            <xs:element name="NonLinear" minOccurs="0" maxOccurs="unbounded"
type="NonLinear_type">
                                <xs:annotation>
                                    <xs:documentation>Any number of companions in any desired
pixel dimensions.</xs:documentation>
                                </xs:annotation>
                            </xs:element>
                        </xs:sequence>
                    </xs:complexType>
                </xs:element>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
<xs:attribute name="id" type="xs:string" use="optional"/>
<xs:attribute name="sequence" type="xs:integer" use="optional">
    <xs:annotation>
        <xs:documentation>The preferred order in which multiple Creatives
should be displayed</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="AdID" type="xs:string" use="optional">
    <xs:annotation>
        <xs:documentation>Ad-ID for the creative (formerly ISCI)</
xs:documentation>
    </xs:annotation>
</xs:attribute>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Extensions" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Extension" type="xs:anyType" minOccurs="0"
maxOccurs="unbounded">
                <xs:annotation>
                    <xs:documentation>Any valid XML may be included in the Extensions node</
xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

Element Wrapper / Ad / VAST / AdSystem

Namespace	No namespace
Annotations	Indicates source ad server
Diagram	<pre> classDiagram class AdSystem { <<AdSystem_type>> Type AdSystem_type } class xsString { <<xs:string>> } class attributes { <<@ attributes>> } class version { <<@ version>> Type xsString } AdSystem < -- xsString AdSystem < -- attributes AdSystem < -- version </pre>

Type	AdSystem_type				
Properties	content: complex minOccurs: 1 maxOccurs: 1				
Attributes	QName Type Fixed Default Use version xs:string optional Internal version used by ad system				
Source	<pre><xs:element name="AdSystem" type="AdSystem_type" maxOccurs="1" minOccurs="1"> <xs:annotation> <xs:documentation>Indicates source ad server</xs:documentation> </xs:annotation> </xs:element></pre>				


Element Wrapper / Ad / VAST / VASTAdTagURI

Namespace	No namespace				
Annotations	URL of ad tag of downstream Secondary Ad Server				
Diagram					
Type	xs:anyURI				
Properties	content: simple minOccurs: 1 maxOccurs: 1				
Source	<pre><xs:element name="VASTAdTagURI" type="xs:anyURI" maxOccurs="1" minOccurs="1"> <xs:annotation> <xs:documentation>URL of ad tag of downstream Secondary Ad Server</xs:documentation> </xs:annotation> </xs:element></pre>				

Element Wrapper / Ad / VAST / Error

Namespace	No namespace				
Annotations	URL to request if ad does not play due to error				
Diagram					
Type	xs:anyURI				
Properties	content: simple minOccurs: 0 maxOccurs: 1				
Source	<pre><xs:element name="Error" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to request if ad does not play due to error</xs:documentation> </xs:annotation> </xs:element></pre>				

Element Wrapper / Ad / VAST / Impression

Namespace	No namespace				
Annotations	URL to request to track an impression				
Diagram					
Type	xs:anyURI				
Properties	content: simple minOccurs: 1 maxOccurs: unbounded				

Source	<pre><xss:element name="Impression" type="xs:anyURI" maxOccurs="unbounded" minOccurs="1"> <xss:annotation> <xss:documentation>URL to request to track an impression</xss:documentation> </xss:annotation> </xss:element></pre>
--------	--

Element Wrapper / Ad / VAST / Creatives

Namespace	No namespace
Diagram	
Properties	content: complex
Model	Creative*
Children	Creative
Instance	<pre><Creatives> <Creative AdID="" id="" sequence="">{0,unbounded}</Creative> </Creatives></pre>
Source	<pre><xss:element name="Creatives"> <xss:complexType> <xss:sequence> <xss:element name="Creative" maxOccurs="unbounded" minOccurs="0"> <xss:complexType> <xss:choice> <xss:element name="Linear" minOccurs="0" maxOccurs="1"> <xss:complexType> <xss:sequence> <xss:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> <xss:element> <xss:complexType> <xss:sequence> <xss:element name="ClickTracking" minOccurs="0" maxOccurs="unbounded"> <xss:annotation> <xss:documentation>URL to request for tracking purposes when user clicks on the video</xss:documentation> </xss:annotation> <xss:complexType> <xss:simpleContent> <xss:extension base="xs:anyURI"> <xss:attribute name="id" type="xs:string" use="optional"/> </xss:extension> </xss:simpleContent> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:element> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:element> </xss:choice> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:element> <xss:element name="CompanionAds" minOccurs="0" maxOccurs="1"> <xss:complexType> <xss:sequence> <xss:element name="Companion" minOccurs="0" maxOccurs="unbounded" type="Companion_type"> <xss:annotation> <xss:documentation>Definition of Companion ad, if served separately</ xs:documentation> </xss:annotation> </xss:element> </xss:sequence> </xss:complexType> </xss:element> <xss:element name="NonLinearAds" minOccurs="0" maxOccurs="1"> <xss:complexType> <xss:sequence> <xss:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> <xss:element> <xss:complexType> <xss:sequence> <xss:element name="NonLinear" minOccurs="0" maxOccurs="unbounded" type="NonLinear_type"> <xss:annotation> <xss:documentation>Any number of companions in any desired pixel dimensions.</xss:documentation> </xss:annotation> </xss:element> </xss:sequence> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:element></pre>

```

        </xs:element>
    </xs:sequence>
</xs:complexType>
</xs:element>
</xs:choice>
<xs:attribute name="id" type="xs:string" use="optional"/>
<xs:attribute name="sequence" type="xs:integer" use="optional">
    <xs:annotation>
        <xs:documentation>The preferred order in which multiple Creatives should be displayed</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="AdID" type="xs:string" use="optional">
    <xs:annotation>
        <xs:documentation>Ad-ID for the creative (formerly ISCI)</xs:documentation>
    </xs:annotation>
</xs:attribute>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

Element Creatives / Wrapper / Ad / VAST / Creative

Namespace	No namespace																														
Diagram	<pre> classDiagram class Creative { @ attributes @ id Type xs:string @ sequence Type xs:integer @ AdID Type xs:string } class Linear class CompanionAds class NonLinearAds Creative "0..1" -- "0..1" Linear Creative "0..1" -- "0..1" CompanionAds Creative "0..1" -- "0..1" NonLinearAds </pre>																														
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: unbounded</p>																														
Model	Linear{0,1} CompanionAds{0,1} NonLinearAds{0,1}																														
Children	CompanionAds, Linear, NonLinearAds																														
Instance	<Creative AdID="" id="" sequence=""> <Linear>{0,1}</Linear> <CompanionAds>{0,1}</CompanionAds> <NonLinearAds>{0,1}</NonLinearAds> </Creative>																														
Attributes	<table border="1"> <thead> <tr> <th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th></tr> </thead> <tbody> <tr> <td>AdID</td><td>xs:string</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">Ad-ID for the creative (formerly ISCI)</td></tr> <tr> <td>id</td><td>xs:string</td><td></td><td></td><td>optional</td></tr> <tr> <td>sequence</td><td>xs:integer</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">The preferred order in which multiple Creatives should be displayed</td></tr> </tbody> </table>	QName	Type	Fixed	Default	Use	AdID	xs:string			optional		Ad-ID for the creative (formerly ISCI)				id	xs:string			optional	sequence	xs:integer			optional		The preferred order in which multiple Creatives should be displayed			
QName	Type	Fixed	Default	Use																											
AdID	xs:string			optional																											
	Ad-ID for the creative (formerly ISCI)																														
id	xs:string			optional																											
sequence	xs:integer			optional																											
	The preferred order in which multiple Creatives should be displayed																														
Source	<pre> <xs:element name="Creative" maxOccurs="unbounded" minOccurs="0"> <xs:complexType> <xs:choice> <xs:element name="Linear" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xs:element> <xs:element name="VideoClicks" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> </pre>																														

```

<xs:element name="ClickTracking" minOccurs="0" maxOccurs="unbounded">
    <xs:annotation>
        <xs:documentation>URL to request for tracking purposes when user
clicks on the video</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:simpleContent>
            <xs:extension base="xs:anyURI">
                <xs:attribute name="id" type="xs:string" use="optional"/>
            </xs:extension>
        </xs:simpleContent>
    </xs:complexType>
    </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CompanionAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Companion" minOccurs="0" maxOccurs="unbounded"
type="Companion_type">
                <xs:annotation>
                    <xs:documentation>Definition of Companion ad, if served separately</
xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type"
maxOccurs="1">
                <xs:element>
                    <xs:element name="NonLinear" minOccurs="0" maxOccurs="unbounded"
type="NonLinear_type">
                        <xs:annotation>
                            <xs:documentation>Any number of companions in any desired pixel
dimensions.</xs:documentation>
                        </xs:annotation>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:choice>
    <xs:attribute name="id" type="xs:string" use="optional"/>
    <xs:attribute name="sequence" type="xs:integer" use="optional">
        <xs:annotation>
            <xs:documentation>The preferred order in which multiple Creatives should be
displayed</xs:documentation>
        </xs:annotation>
    </xs:attribute>
    <xs:attribute name="AdID" type="xs:string" use="optional">
        <xs:annotation>
            <xs:documentation>Ad-ID for the creative (formerly ISCI)</xs:documentation>
        </xs:annotation>
    </xs:attribute>
</xs:choice>
</xs:complexType>
</xs:element>

```

Element Creative / Creatives / Wrapper / Ad / VAST / Linear

Namespace	No namespace						
Diagram	<pre> classDiagram class Linear class TrackingEvents { <<Type>> <<TrackingEvents_type>> } class VideoClicks Linear --> TrackingEvents TrackingEvents --> Type TrackingEvents --> VideoClicks </pre>						
Properties	<table border="1"> <tbody> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </tbody> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	TrackingEvents{0,1} , VideoClicks{0,1}						
Children	TrackingEvents, VideoClicks						

Instance	<pre><Linear> <TrackingEvents>{0,1}</TrackingEvents> <VideoClicks>{0,1}</VideoClicks> </Linear></pre>
Source	<pre><xs:element name="Linear" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xs:element> <xs:element name="VideoClicks" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> <xs:element name="ClickTracking" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>URL to request for tracking purposes when user clicks on the video</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

Element Linear / Creative / Creatives / Wrapper / Ad / VAST / TrackingEvents

Namespace	No namespace						
Diagram	<pre> classDiagram class TrackingEvents_type { <<TrackingEvents>> <<Type TrackingEvents_type>> } class Tracking { <<Tracking>> <<Type extension of 'xs:anyURI'>> } TrackingEvents_type "0..∞" -- "0..∞" Tracking : ClickTracking </pre>						
Type	TrackingEvents_type						
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	Tracking*						
Children	Tracking						
Instance	<pre><TrackingEvents> <Tracking event="">{0,unbounded}</Tracking> </TrackingEvents></pre>						
Source	<pre><xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xs:element></pre>						

Element Linear / Creative / Creatives / Wrapper / Ad / VAST / VideoClicks

Namespace	No namespace						
Diagram	<pre> classDiagram class VideoClicks { <<VideoClicks>> } class ClickTracking { <<ClickTracking>> <<Type extension of 'xs:anyURI'>> } VideoClicks "0..∞" -- "0..∞" ClickTracking : ClickTracking </pre>						
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	ClickTracking*						
Children	ClickTracking						
Instance	<pre><VideoClicks> <ClickTracking id="">{0,unbounded}</ClickTracking> </VideoClicks></pre>						

Source	<pre> <xss:element name="VideoClicks" minOccurs="0" maxOccurs="1"> <xss:complexType> <xss:sequence> <xss:element name="ClickTracking" minOccurs="0" maxOccurs="unbounded"> <xss:annotation> <xss:documentation>URL to request for tracking purposes when user clicks on the video</xss:documentation> </xss:annotation> <xss:complexType> <xss:simpleContent> <xss:extension base="xs:anyURI"> <xss:attribute name="id" type="xs:string" use="optional"/> </xss:extension> </xss:simpleContent> </xss:complexType> </xss:element> </xss:sequence> </xss:complexType> </xss:element> </pre>
--------	--

Element VideoClicks / Linear / Creative / Creatives / Wrapper / Ad / VAST / ClickTracking

Namespace	No namespace										
Annotations	URL to request for tracking purposes when user clicks on the video										
Diagram	<pre> classDiagram ClickTracking < -- xs:anyURI ClickTracking { @ id : xs:string } </pre>										
Type	extension of xs:anyURI										
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>unbounded</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	unbounded				
content:	complex										
minOccurs:	0										
maxOccurs:	unbounded										
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>xs:string</td> <td></td> <td></td> <td>optional</td> </tr> </tbody> </table>	QName	Type	Fixed	Default	Use	id	xs:string			optional
QName	Type	Fixed	Default	Use							
id	xs:string			optional							
Source	<pre> <xss:element name="ClickTracking" minOccurs="0" maxOccurs="unbounded"> <xss:annotation> <xss:documentation>URL to request for tracking purposes when user clicks on the video</xss:documentation> </xss:annotation> <xss:complexType> <xss:simpleContent> <xss:extension base="xs:anyURI"> <xss:attribute name="id" type="xs:string" use="optional"/> </xss:extension> </xss:simpleContent> </xss:complexType> </xss:element> </pre>										

Element Creative / Creatives / Wrapper / Ad / VAST / CompanionAds

Namespace	No namespace						
Diagram	<pre> classDiagram CompanionAds *-- Companion : Companion_type </pre>						
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>1</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	Companion*						
Children	Companion						
Instance	<pre> <CompanionAds> <Companion apiFramework="" expandedHeight="" expandedWidth="" height="" id="" width="">{0,unbounded}</Companion> </CompanionAds> </pre>						


Source	<pre><xss:element name="CompanionAds" minOccurs="0" maxOccurs="1"> <xss:complexType> <xss:sequence> <xss:element name="Companion" minOccurs="0" maxOccurs="unbounded" type="Companion_type"> <xss:annotation> <xss:documentation>Definition of Companion ad, if served separately</xss:documentation> </xss:annotation> </xss:element> </xss:sequence> </xss:complexType> </xss:element></pre>
--------	--

Element CompanionAds / Creative / Creatives / Wrapper / Ad / VAST / Companion

Namespace	No namespace						
Annotations	Definition of Companion ad, if served separately						
Diagram	<p>The diagram illustrates the structure of the <code>Companion_type</code>. It includes the following components:</p> <ul style="list-style-type: none"> Attributes: <ul style="list-style-type: none"> <code>@ id</code>: Type <code>xs:string</code> <code>@ width</code>: Type <code>xs:integer</code> <code>@ height</code>: Type <code>xs:integer</code> <code>@ expandedWidth</code>: Type <code>xs:integer</code> <code>@ expandedHeight</code>: Type <code>xs:integer</code> <code>@ apiFramework</code>: Type <code>xs:string</code> Associations: <ul style="list-style-type: none"> A multiplicity association from <code>Companion</code> (Type <code>Companion_type</code>) to <code>StaticResource</code>. A multiplicity association from <code>Companion</code> to <code>IframeResource</code>. A multiplicity association from <code>Companion</code> to <code>HTMLResource</code>. A multiplicity association from <code>Companion</code> to <code>TrackingEvents</code>. A multiplicity association from <code>Companion</code> to <code>CompanionClickThrough</code>. A multiplicity association from <code>Companion</code> to <code>AltText</code>. A multiplicity association from <code>Companion</code> to <code>AdParameters</code>. 						
Type	<code>Companion_type</code>						
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> <tr> <td>maxOccurs:</td> <td>unbounded</td> </tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	unbounded
content:	complex						
minOccurs:	0						
maxOccurs:	unbounded						
Model	(<code>StaticResource{0,1}</code> <code>IframeResource{0,1}</code> <code>HTMLResource{0,1}</code>) , <code>TrackingEvents{0,1}</code> , <code>CompanionClickThrough{0,1}</code> , <code>AltText{0,1}</code> , <code>AdParameters{0,1}</code>						
Children	<code>AdParameters</code> , <code>AltText</code> , <code>CompanionClickThrough</code> , <code>HTMLResource</code> , <code>IframeResource</code> , <code>StaticResource</code> , <code>TrackingEvents</code>						
Instance	<pre><Companion apiFramework="" expandedHeight="" expandedWidth="" height="" id="" width=""> <StaticResource creativeType="">{0,1}</StaticResource> <IframeResource>{0,1}</IframeResource></pre>						


	<HTMLResource>{0,1}</HTMLResource> <TrackingEvents>{0,1}</TrackingEvents> <CompanionClickThrough>{0,1}</CompanionClickThrough> <AltText>{0,1}</AltText> <AdParameters>{0,1}</AdParameters> </Companion>				
Attributes	QName	Type	Fixed	Default	Use
	apiFramework	xs:string			optional
	The apiFramework defines the method to use for communication with the companion				
	expandedHeight	xs:integer			optional
	Pixel dimensions of expanding companion ad when in expanded state				
	expandedWidth	xs:integer			optional
	Pixel dimensions of expanding companion ad when in expanded state				
	height	xs:integer			required
	Pixel dimensions of companion				
	id	xs:string			optional
	Optional identifier				
	width	xs:integer			required
	Pixel dimensions of companion				
Source	<xs:element name="Companion" minOccurs="0" maxOccurs="unbounded" type="Companion_type"> <xs:annotation> <xs:documentation>Definition of Companion ad, if served separately</xs:documentation> </xs:annotation> </xs:element>				

Element Creative / Creatives / Wrapper / Ad / VAST / NonLinearAds


Namespace	No namespace
Diagram	
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Model	TrackingEvents{0,1} , NonLinear*
Children	NonLinear, TrackingEvents
Instance	<NonLinearAds> <TrackingEvents>{0,1}</TrackingEvents> <NonLinear apiFramework="" expandedHeight="" expandedWidth="" height="" id="" maintainAspectRatio="" NonLinear> </NonLinearAds>
Source	<xs:element name="NonLinearAds" minOccurs="0" maxOccurs="1"> <xs:complexType> <xs:sequence> <xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xs:element> <xs:element name="NonLinear" minOccurs="0" maxOccurs="unbounded" type="NonLinear_type"> <xs:annotation> <xs:documentation>Any number of companions in any desired pixel dimensions.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element>

Element NonLinearAds / Creative / Creatives / Wrapper / Ad / VAST / TrackingEvents

Namespace	No namespace
-----------	--------------


Diagram	
Type	TrackingEvents_type
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Model	Tracking*
Children	Tracking
Instance	<TrackingEvents> <Tracking event="">{0,unbounded}</Tracking> </TrackingEvents>
Source	<xs:element name="TrackingEvents" minOccurs="0" type="TrackingEvents_type" maxOccurs="1"> </xs:element>

Element NonLinearAds / Creative / Creatives / Wrapper / Ad / VAST / NonLinear

Namespace	No namespace
Annotations	Any number of companions in any desired pixel dimensions.
Diagram	
Type	NonLinear_type
Properties	content: complex

	minOccurs:	0			
	maxOccurs:	unbounded			
Model	(StaticResource{0,1} IFrameResource{0,1} HTMLResource{0,1}) , NonLinearClickThrough{0,1} , AdParameters{0,1}				
Children	AdParameters, HTMLResource, IFrameResource, NonLinearClickThrough, StaticResource				
Instance	<NonLinear apiFramework="" expandedHeight="" expandedWidth="" height="" id="" maintainAspectRatio="" minSuggestedDuration="" scalable="" width=""><StaticResource creativeType="">{0,1}</StaticResource><IFrameResource>{0,1}</IFrameResource><HTMLResource>{0,1}</HTMLResource><NonLinearClickThrough>{0,1}</NonLinearClickThrough><AdParameters>{0,1}</AdParameters></NonLinear>				
Attributes	QName	Type	Fixed	Default	Use
	apiFramework	xs:string			optional
		The apiFramework defines the method to use for communication with the nonlinear element			
	expandedHeight	xs:integer			optional
		Pixel dimensions of expanding nonlinear ad when in expanded state			
	expandedWidth	xs:integer			optional
		Pixel dimensions of expanding nonlinear ad when in expanded state			
	height	xs:integer			required
		Pixel dimensions of companion			
	id	xs:string			optional
		Optional identifier			
	maintainAspectRatio	xs:boolean			optional
		Whether the ad must have its aspect ratio maintained when scales			
	minSuggestedDuration	xs:time			optional
		Suggested duration to display non-linear ad, typically for animation to complete. Expressed in standard time format hh:mm:ss			
	scalable	xs:boolean			optional
		Whether it is acceptable to scale the image.			
	width	xs:integer			required
		Pixel dimensions of companion			
Source	<xss:element name="NonLinear" minOccurs="0" maxOccurs="unbounded" type="NonLinear_type"><xss:annotation><xss:documentation>Any number of companions in any desired pixel dimensions.</xss:documentation></xss:annotation></xss:element>				

Element Wrapper / Ad / VAST / Extensions

Namespace	No namespace
Diagram	
Properties	<p>content: complex</p> <p>minOccurs: 0</p> <p>maxOccurs: 1</p>
Model	Extension*
Children	Extension
Instance	<Extensions><Extension>{0,unbounded}</Extension></Extensions>
Source	<xss:element name="Extensions" minOccurs="0" maxOccurs="1"><xss:complexType><xss:sequence><xss:element name="Extension" type="xs:anyType" minOccurs="0" maxOccurs="unbounded"><xss:annotation>

```

<xs:documentation>Any valid XML may be included in the Extensions node</
xs:documentation>
</xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

Element Extensions / Wrapper / Ad / VAST / Extension

Namespace	No namespace
Annotations	Any valid XML may be included in the Extensions node
Diagram	<pre> classDiagram class Extension { <<xs:anyType>> @ attributes : #any } Extension < -- xs:anyType </pre>
Properties	minOccurs: 0 maxOccurs: unbounded
Source	<pre> <xs:element name="Extension" type="xs:anyType" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Any valid XML may be included in the Extensions node</ xs:documentation> </xs:annotation> </xs:element> </pre>


Complex Types

Complex Type AdSystem_type


Namespace	No namespace															
Diagram	<pre> classDiagram class AdSystem_type { <<xs:string>> @ version : xs:string } AdSystem_type < -- xs:string </pre>															
Type	extension of xs:string															
Used by	Elements VAST/Ad/InLine/AdSystem, VAST/Ad/Wrapper/AdSystem															
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>version</td> <td>xs:string</td> <td></td> <td></td> <td>optional</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Internal version used by ad system</td> </tr> </tbody> </table>	QName	Type	Fixed	Default	Use	version	xs:string			optional					Internal version used by ad system
QName	Type	Fixed	Default	Use												
version	xs:string			optional												
				Internal version used by ad system												
Source	<pre> <xs:complexType name="AdSystem_type"> <xs:simpleContent> <xs:extension base="xs:string"> <xs:attribute name="version" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Internal version used by ad system</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </pre>															

Complex Type Impression_type

Namespace	No namespace
-----------	--------------

Diagram											
Type	extension of xs:anyURI										
Used by	Element VAST/Ad/InLine/Impression										
Attributes	<table border="1"> <thead> <tr> <th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th></tr> </thead> <tbody> <tr> <td>id</td><td>xs:string</td><td></td><td></td><td>optional</td></tr> </tbody> </table>	QName	Type	Fixed	Default	Use	id	xs:string			optional
QName	Type	Fixed	Default	Use							
id	xs:string			optional							
Source	<pre><xs:complexType name="Impression_type"> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"/> </xs:extension> </xs:simpleContent> </xs:complexType></pre>										

Complex Type TrackingEvents_type

Namespace	No namespace
Diagram	
Used by	Elements Companion_type/TrackingEvents, VAST/Ad/InLine/Creatives/Creative/Linear/ TrackingEvents, VAST/Ad/InLine/Creatives/Creative/NonLinearAds/TrackingEvents, VAST/Ad/Wrapper/Creatives/Creative/Linear/TrackingEvents, VAST/Ad/Wrapper/ Creatives/Creative/NonLinearAds/TrackingEvents
Model	Tracking*
Children	Tracking
Source	<pre><xs:complexType name="TrackingEvents_type"> <xs:sequence> <xs:element name="Tracking" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>The name of the event to track for the Linear element. The creativeView should always be requested when present.</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="event" use="required"> <xs:annotation> <xs:documentation>The name of the event to track. For nonlinear ads these events should be recorded on the video within the ad.</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="creativeView"/> <xs:enumeration value="start"/> <xs:enumeration value="midpoint"/> <xs:enumeration value="firstQuartile"/> <xs:enumeration value="thirdQuartile"/> <xs:enumeration value="complete"/> <xs:enumeration value="mute"/> <xs:enumeration value="unmute"/> <xs:enumeration value="pause"/> <xs:enumeration value="rewind"/> <xs:enumeration value="resume"/> <xs:enumeration value="fullscreen"/> <xs:enumeration value="expand"/> <xs:enumeration value="collapse"/> <xs:enumeration value="acceptInvitation"/> <xs:enumeration value="close"/> </xs:restriction> </xs:simpleType> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence></pre>

</xs:complexType>


Complex Type VideoClicks_type

Namespace	No namespace
Diagram	<pre> classDiagram class VideoClicks_type { <<VideoClicks type>> <<ClickThrough
Type extension of 'xs:anyURI'>> <<ClickTracking
Type extension of 'xs:anyURI'>> <<CustomClick
Type extension of 'xs:anyURI'>> } ClickThrough < -- VideoClicks_type ClickTracking < -- VideoClicks_type CustomClick < -- VideoClicks_type </pre>
Used by	Element VAST/Ad/InLine/Creatives/Creative/Linear/VideoClicks
Model	ClickThrough{0,1} , ClickTracking* , CustomClick*
Children	ClickThrough, ClickTracking, CustomClick
Source	<pre> <xs:complexType name="VideoClicks_type"> <xs:sequence> <xs:element name="ClickThrough" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to open as destination page when user clicks on the video</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element name="ClickTracking" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>URL to request for tracking purposes when user clicks on the video</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element name="CustomClick" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>URLs to request on custom events such as hotspotted video</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="id" type="xs:string" use="optional"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </pre>

Complex Type Companion_type

Namespace	No namespace
-----------	--------------

Diagram



Used by

Elements VAST/Ad/InLine/Creatives/Creative/CompanionAds/Companion, VAST/Ad/Wrapper/Creatives/Creative/CompanionAds/Companion

Model

`(StaticResource{0,1} | IFrameResource{0,1} | HTMLResource{0,1}) , TrackingEvents{0,1} , CompanionClickThrough{0,1} , AltText{0,1} , AdParameters{0,1}`

Children

AdParameters, AltText, CompanionClickThrough, HTMLResource, IFrameResource, StaticResource, TrackingEvents

Attributes

QName	Type	Fixed	Default	Use
apiFramework	<code>xs:string</code>			optional
The <code>apiFramework</code> defines the method to use for communication with the companion				
expandedHeight	<code>xs:integer</code>			optional
Pixel dimensions of expanding companion ad when in expanded state				
expandedWidth	<code>xs:integer</code>			optional
Pixel dimensions of expanding companion ad when in expanded state				
height	<code>xs:integer</code>			required
Pixel dimensions of companion				
id	<code>xs:string</code>			optional
Optional identifier				
width	<code>xs:integer</code>			required
Pixel dimensions of companion				

Source

```

<xs:complexType name="Companion_type">
    <xs:sequence>
        <xs:choice>
            <xs:element name="StaticResource" minOccurs="0" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation>URL to a static file, such as an image or SWF file</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:choice>
    </xs:sequence>
</xs:complexType>

```

```

        </xs:annotation>
    <xs:complexType>
        <xs:simpleContent>
            <xs:extension base="xs:anyURI">
                <xs:attribute name="creativeType" type="xs:string" use="required">
                    <xs:annotation>
                        <xs:documentation>Mime type of static resource</xs:documentation>
                    </xs:annotation>
                </xs:attribute>
            </xs:extension>
        </xs:simpleContent>
    </xs:complexType>
    <xs:element>
        <xs:element name="IFrameResource" type="xs:anyURI" minOccurs="0" maxOccurs="1">
            <xs:annotation>
                <xs:documentation>URL source for an IFrame to display the companion element</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="HTMLResource" type="xs:string" minOccurs="0" maxOccurs="1">
            <xs:annotation>
                <xs:documentation>HTML to display the companion element</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:choice>
    <xs:element maxOccurs="1" minOccurs="0" name="TrackingEvents" type="TrackingEvents_type">
        <xs:annotation>
            <xs:documentation>The creativeView should always be requested when present. For Companions creativeView is the only supported event.</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="CompanionClickThrough" type="xs:anyURI" minOccurs="0" maxOccurs="1">
        <xs:annotation>
            <xs:documentation>URL to open as destination page when user clicks on the the companion banner ad.</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="AltText" type="xs:string" minOccurs="0" maxOccurs="1">
        <xs:annotation>
            <xs:documentation>Alt text to be displayed when companion is rendered in HTML environment.</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1">
        <xs:annotation>
            <xs:documentation>Data to be passed into the companion ads. The apiFramework defines the method to use for communication (e.g. "FlashVar")</xs:documentation>
        </xs:annotation>
    </xs:element>
</xs:sequence>
<xs:attribute name="id" type="xs:string" use="optional">
    <xs:annotation>
        <xs:documentation>Optional identifier</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="width" type="xs:integer" use="required">
    <xs:annotation>
        <xs:documentation>Pixel dimensions of companion</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="height" type="xs:integer" use="required">
    <xs:annotation>
        <xs:documentation>Pixel dimensions of companion</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="expandedWidth" type="xs:integer" use="optional">
    <xs:annotation>
        <xs:documentation>Pixel dimensions of expanding companion ad when in expanded state</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="expandedHeight" type="xs:integer" use="optional">
    <xs:annotation>
        <xs:documentation>Pixel dimensions of expanding companion ad when in expanded state</xs:documentation>
    </xs:annotation>
</xs:attribute>
<xs:attribute name="apiFramework" type="xs:string" use="optional">
    <xs:annotation>
        <xs:documentation>The apiFramework defines the method to use for communication with the companion</xs:documentation>
    </xs:annotation>

```

```
</xs:attribute>
</xs:complexType>
```

Complex Type NonLinear_type

Namespace	No namespace																																																												
Diagram	<p>The diagram illustrates the structure of the <code>NonLinear_type</code>. It features a central node labeled <code>NonLinear_type</code> with a self-referencing association loop. This loop connects to a box labeled <code>⊕</code>, which then points to a list of child elements: <code>StaticResource</code>, <code>IFrameResource</code>, <code>HTMLResource</code>, <code>NonLinearClickThrough</code>, and <code>AdParameters</code>. Above the <code>NonLinear_type</code> node, a box labeled <code>⊖</code> contains a list of attributes: <code>@ id</code> (Type <code>xs:string</code>), <code>@ width</code> (Type <code>xs:integer</code>), <code>@ height</code> (Type <code>xs:integer</code>), <code>@ expandedWidth</code> (Type <code>xs:integer</code>), <code>@ expandedHeight</code> (Type <code>xs:integer</code>), <code>@ scalable</code> (Type <code>xs:boolean</code>), <code>@ maintainAspectRatio</code> (Type <code>xs:boolean</code>), <code>@ minSuggestedDuration</code> (Type <code>xs:time</code>), and <code>@ apiFramework</code> (Type <code>xs:string</code>). There are also plus signs (+) next to each attribute entry.</p>																																																												
Used by	Elements VAST/Ad/InLine/Creatives/Creative/NonLinearAds/NonLinear, VAST/Ad/Wrapper/Creatives/Creative/NonLinearAds/NonLinear																																																												
Model	<code>(StaticResource{0,1} IFrameResource{0,1} HTMLResource{0,1}) , NonLinearClickThrough{0,1} , AdParameters{0,1}</code>																																																												
Children	AdParameters, HTMLResource, IFrameResource, NonLinearClickThrough, StaticResource																																																												
Attributes	<table border="1"> <thead> <tr> <th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th></tr> </thead> <tbody> <tr> <td>apiFramework</td><td>xs:string</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">The <code>apiFramework</code> defines the method to use for communication with the nonlinear element</td></tr> <tr> <td>expandedHeight</td><td>xs:integer</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">Pixel dimensions of expanding nonlinear ad when in expanded state</td></tr> <tr> <td>expandedWidth</td><td>xs:integer</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">Pixel dimensions of expanding nonlinear ad when in expanded state</td></tr> <tr> <td>height</td><td>xs:integer</td><td></td><td></td><td>required</td></tr> <tr> <td></td><td colspan="4">Pixel dimensions of companion</td></tr> <tr> <td>id</td><td>xs:string</td><td></td><td></td><td>optional</td></tr> <tr> <td></td><td colspan="4">Optional identifier</td></tr> <tr> <td>maintainAspectRatio</td><td>xs:boolean</td><td></td><td></td><td>optional</td></tr> </tbody> </table>	QName	Type	Fixed	Default	Use	apiFramework	xs:string			optional		The <code>apiFramework</code> defines the method to use for communication with the nonlinear element				expandedHeight	xs:integer			optional		Pixel dimensions of expanding nonlinear ad when in expanded state				expandedWidth	xs:integer			optional		Pixel dimensions of expanding nonlinear ad when in expanded state				height	xs:integer			required		Pixel dimensions of companion				id	xs:string			optional		Optional identifier				maintainAspectRatio	xs:boolean			optional
QName	Type	Fixed	Default	Use																																																									
apiFramework	xs:string			optional																																																									
	The <code>apiFramework</code> defines the method to use for communication with the nonlinear element																																																												
expandedHeight	xs:integer			optional																																																									
	Pixel dimensions of expanding nonlinear ad when in expanded state																																																												
expandedWidth	xs:integer			optional																																																									
	Pixel dimensions of expanding nonlinear ad when in expanded state																																																												
height	xs:integer			required																																																									
	Pixel dimensions of companion																																																												
id	xs:string			optional																																																									
	Optional identifier																																																												
maintainAspectRatio	xs:boolean			optional																																																									

QName	Type	Fixed	Default	Use
		Whether the ad must have its aspect ratio maintained when scales		
minSuggestedDuration	xs:time			optional
		Suggested duration to display non-linear ad, typically for animation to complete. Expressed in standard time format hh:mm:ss		
scalable	xs:boolean			optional
		Whether it is acceptable to scale the image.		
width	xs:integer			required
		Pixel dimensions of companion		
Source	<pre> <xs:complexType name="NonLinear_type"> <xs:sequence> <xs:choice> <xs:element name="StaticResource" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to a static file, such as an image or SWF file</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:anyURI"> <xs:attribute name="creativeType" type="xs:string" use="required"> <xs:annotation> <xs:documentation>Mime type of static resource</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element name="IFrameResource" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL source for an IFrame to display the companion element</xs:documentation> </xs:annotation> </xs:element> <xs:element name="HTMLResource" type="xs:string" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>HTML to display the companion element</xs:documentation> </xs:annotation> </xs:element> </xs:choice> <xs:element name="NonLinearClickThrough" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>URL to open as destination page when user clicks on the the non-linear ad unit.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="AdParameters" type="xs:string" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation>Data to be passed into the video ad.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> <xs:attribute name="id" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Optional identifier</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="width" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of companion</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="height" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of companion</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="expandedWidth" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>Pixel dimensions of expanding nonlinear ad when in expanded state</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="expandedHeight" type="xs:integer" use="optional"> <xs:annotation> </pre>			

```

<xs:documentation>Pixel dimensions of expanding nonlinear ad when in expanded
state</xs:documentation>
</xs:annotation>
</xs:attribute>
<xs:attribute name="scalable" type="xs:boolean" use="optional">
<xs:annotation>
<xs:documentation>Whether it is acceptable to scale the image.</xs:documentation>
</xs:annotation>
</xs:attribute>
<xs:attribute name="maintainAspectRatio" type="xs:boolean" use="optional">
<xs:annotation>
<xs:documentation>Whether the ad must have its aspect ratio maintained when scales</
xs:documentation>
</xs:annotation>
</xs:attribute>
<xs:attribute name="minSuggestedDuration" type="xs:time" use="optional">
<xs:annotation>
<xs:documentation>Suggested duration to display non-linear ad, typically for
animation to complete. Expressed in standard time format hh:mm:ss</xs:documentation>
</xs:annotation>
</xs:attribute>
<xs:attribute name="apiFramework" type="xs:string" use="optional">
<xs:annotation>
<xs:documentation>The apiFramework defines the method to use for communication with
the nonlinear element</xs:documentation>
</xs:annotation>
</xs:attribute>
</xs:complexType>

```

Attributes

Attribute AdSystem_type / @version

Namespace	No namespace
Annotations	Internal version used by ad system
Type	xs:string
Properties	use: optional
Used by	Complex Type AdSystem_type
Source	<xs:attribute name="version" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Internal version used by ad system</xs:documentation> </xs:annotation> </xs:attribute>

Attribute Impression_type / @id

Namespace	No namespace
Type	xs:string
Properties	use: optional
Used by	Complex Type Impression_type
Source	<xs:attribute name="id" type="xs:string" use="optional"/>

Attribute Tracking / TrackingEvents_type / @event

Namespace	No namespace
Annotations	The name of the event to track. For nonlinear ads these events should be recorded on the video within the ad.
Type	restriction of xs:NMTOKEN
Properties	use: required
Facets	enumeration creativeView enumeration start enumeration midpoint enumeration firstQuartile enumeration thirdQuartile enumeration complete

	enumeration	mute
	enumeration	unmute
	enumeration	pause
	enumeration	rewind
	enumeration	resume
	enumeration	fullscreen
	enumeration	expand
	enumeration	collapse
	enumeration	acceptInvitation
	enumeration	close
Used by	Element	TrackingEvents_type/Tracking
Source	<pre><xs:attribute name="event" use="required"> <xs:annotation> <xs:documentation>The name of the event to track. For nonlinear ads these events should be recorded on the video within the ad.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="creativeView"/> <xs:enumeration value="start"/> <xs:enumeration value="midpoint"/> <xs:enumeration value="firstQuartile"/> <xs:enumeration value="thirdQuartile"/> <xs:enumeration value="complete"/> <xs:enumeration value="mute"/> <xs:enumeration value="unmute"/> <xs:enumeration value="pause"/> <xs:enumeration value="rewind"/> <xs:enumeration value="resume"/> <xs:enumeration value="fullscreen"/> <xs:enumeration value="expand"/> <xs:enumeration value="collapse"/> <xs:enumeration value="acceptInvitation"/> <xs:enumeration value="close"/> </xs:restriction> </xs:simpleType> </xs:attribute></pre>	

Attribute ClickThrough / VideoClicks_type / @id

Namespace	No namespace
Type	xs:string
Properties	use: optional
Used by	Element VideoClicks_type/ClickThrough
Source	<xs:attribute name="id" type="xs:string" use="optional"/>

Attribute ClickTracking / VideoClicks_type / @id

Namespace	No namespace
Type	xs:string
Properties	use: optional
Used by	Element VideoClicks_type/ClickTracking
Source	<xs:attribute name="id" type="xs:string" use="optional"/>

Attribute CustomClick / VideoClicks_type / @id

Namespace	No namespace
Type	xs:string
Properties	use: optional
Used by	Element VideoClicks_type/CustomClick

Source	<pre><xs:attribute name="id" type="xs:string" use="optional"/></pre>
--------	--

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @id

Namespace	No namespace
Annotations	Optional identifier
Type	xs:string
Properties	use: optional
Used by	Element VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile
Source	<pre><xs:attribute name="id" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Optional identifier</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @delivery

Namespace	No namespace
Annotations	Method of delivery of ad
Type	restriction of xs:NMTOKEN
Properties	use: required
Facets	enumeration streaming enumeration progressive
Used by	Element VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile
Source	<pre><xs:attribute name="delivery" use="required"> <xs:annotation> <xs:documentation>Method of delivery of ad</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:NMTOKEN"> <xs:enumeration value="streaming"/> <xs:enumeration value="progressive"/> </xs:restriction> </xs:simpleType> </xs:attribute></pre>

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @type

Namespace	No namespace
Annotations	MIME type. Popular MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles section with appropriate Mime types
Type	xs:string
Properties	use: required
Used by	Element VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile
Source	<pre><xs:attribute name="type" use="required" type="xs:string"> <xs:annotation> <xs:documentation>MIME type. Popular MIME types include, but are not limited to "video/x-ms-wmv" for Windows Media, and "video/x-flv" for Flash Video. Image ads or interactive ads can be included in the MediaFiles section with appropriate Mime types</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @bitrate

Namespace	No namespace
-----------	--------------

Annotations	Bitrate of encoded video in Kbps	
Type	xs:integer	
Properties	use: optional	
Used by	Element	VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile
Source	<pre><xs:attribute name="bitrate" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>Bitrate of encoded video in Kbps</xs:documentation> </xs:annotation> </xs:attribute></pre>	

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @width

Namespace	No namespace
Annotations	Pixel dimensions of video
Type	xs:integer
Properties	use: required
Used by	Element VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile
Source	<pre><xs:attribute name="width" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of video</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @height

Namespace	No namespace
Annotations	Pixel dimensions of video
Type	xs:integer
Properties	use: required
Used by	Element VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile
Source	<pre><xs:attribute name="height" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of video</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @scalable

Namespace	No namespace
Annotations	Whether it is acceptable to scale the image.
Type	xs:boolean
Properties	use: optional
Used by	Element VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile
Source	<pre><xs:attribute name="scalable" type="xs:boolean" use="optional"> <xs:annotation> <xs:documentation>Whether it is acceptable to scale the image.</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @maintainAspectRatio

Namespace	No namespace
Annotations	Whether the ad must have its aspect ratio maintained when scales
Type	xs:boolean

Properties	use:	optional
Used by	Element	VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile
Source	<xs:attribute name="maintainAspectRatio" type="xs:boolean" use="optional"> <xs:annotation> <xs:documentation>Whether the ad must have its aspect ratio maintained when scales</xs:documentation> </xs:annotation> </xs:attribute>	

Attribute MediaFile / MediaFiles / Linear / Creative / Creatives / InLine / Ad / VAST / @apiFramework

Namespace	No namespace	
Annotations	The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).	
Type	xs:string	
Properties	use: optional	
Used by	Element VAST/Ad/InLine/Creatives/Creative/Linear/MediaFiles/MediaFile	
Source	<xs:attribute name="apiFramework" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>The apiFramework defines the method to use for communication if the MediaFile is interactive. Suggested values for this element are "VPAID", "FlashVars" (for Flash/Flex), "initParams" (for Silverlight) and "GetVariables" (variables placed in key/value pairs on the asset request).</xs:documentation> </xs:annotation> </xs:attribute>	

Attribute StaticResource / Companion_type / @creativeType

Namespace	No namespace	
Annotations	Mime type of static resource	
Type	xs:string	
Properties	use: required	
Used by	Element Companion_type/StaticResource	
Source	<xs:attribute name="creativeType" type="xs:string" use="required"> <xs:annotation> <xs:documentation>Mime type of static resource</xs:documentation> </xs:annotation> </xs:attribute>	

Attribute Companion_type / @id

Namespace	No namespace	
Annotations	Optional identifier	
Type	xs:string	
Properties	use: optional	
Used by	Complex Type Companion_type	
Source	<xs:attribute name="id" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Optional identifier</xs:documentation> </xs:annotation> </xs:attribute>	

Attribute Companion_type / @width

Namespace	No namespace
Annotations	Pixel dimensions of companion
Type	xs:integer
Properties	use: required

Used by	Complex Type	Companion_type
Source	<xs:attribute name="width" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of companion</xs:documentation> </xs:annotation> </xs:attribute>	

Attribute Companion_type / @height

Namespace	No namespace	
Annotations	Pixel dimensions of companion	
Type	xs:integer	
Properties	use: required	
Used by	Complex Type	Companion_type
Source	<xs:attribute name="height" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of companion</xs:documentation> </xs:annotation> </xs:attribute>	

Attribute Companion_type / @expandedWidth

Namespace	No namespace	
Annotations	Pixel dimensions of expanding companion ad when in expanded state	
Type	xs:integer	
Properties	use: optional	
Used by	Complex Type	Companion_type
Source	<xs:attribute name="expandedWidth" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>Pixel dimensions of expanding companion ad when in expanded state</xs:documentation> </xs:annotation> </xs:attribute>	

Attribute Companion_type / @expandedHeight

Namespace	No namespace	
Annotations	Pixel dimensions of expanding companion ad when in expanded state	
Type	xs:integer	
Properties	use: optional	
Used by	Complex Type	Companion_type
Source	<xs:attribute name="expandedHeight" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>Pixel dimensions of expanding companion ad when in expanded state</xs:documentation> </xs:annotation> </xs:attribute>	

Attribute Companion_type / @apiFramework

Namespace	No namespace	
Annotations	The apiFramework defines the method to use for communication with the companion	
Type	xs:string	
Properties	use: optional	
Used by	Complex Type	Companion_type
Source	<xs:attribute name="apiFramework" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>The apiFramework defines the method to use for communication with the companion</xs:documentation> </xs:annotation> </xs:attribute>	

<pre></xs:attribute></pre>

Attribute StaticResource / NonLinear_type / @creativeType

Namespace	No namespace
Annotations	Mime type of static resource
Type	xs:string
Properties	use: required
Used by	Element NonLinear_type/StaticResource
Source	<pre><xs:attribute name="creativeType" type="xs:string" use="required"> <xs:annotation> <xs:documentation>Mime type of static resource</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute NonLinear_type / @id

Namespace	No namespace
Annotations	Optional identifier
Type	xs:string
Properties	use: optional
Used by	Complex Type NonLinear_type
Source	<pre><xs:attribute name="id" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Optional identifier</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute NonLinear_type / @width

Namespace	No namespace
Annotations	Pixel dimensions of companion
Type	xs:integer
Properties	use: required
Used by	Complex Type NonLinear_type
Source	<pre><xs:attribute name="width" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of companion</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute NonLinear_type / @height

Namespace	No namespace
Annotations	Pixel dimensions of companion
Type	xs:integer
Properties	use: required
Used by	Complex Type NonLinear_type
Source	<pre><xs:attribute name="height" type="xs:integer" use="required"> <xs:annotation> <xs:documentation>Pixel dimensions of companion</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute NonLinear_type / @expandedWidth

Namespace	No namespace
Annotations	Pixel dimensions of expanding nonlinear ad when in expanded state
Type	xs:integer

Properties	use: optional
Used by	Complex Type NonLinear_type
Source	<xs:attribute name="expandedWidth" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>Pixel dimensions of expanding nonlinear ad when in expanded state</xs:documentation> </xs:annotation> </xs:attribute>

Attribute NonLinear_type / @expandedHeight

Namespace	No namespace
Annotations	Pixel dimensions of expanding nonlinear ad when in expanded state
Type	xs:integer
Properties	use: optional
Used by	Complex Type NonLinear_type
Source	<xs:attribute name="expandedHeight" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>Pixel dimensions of expanding nonlinear ad when in expanded state</xs:documentation> </xs:annotation> </xs:attribute>

Attribute NonLinear_type / @scalable

Namespace	No namespace
Annotations	Whether it is acceptable to scale the image.
Type	xs:boolean
Properties	use: optional
Used by	Complex Type NonLinear_type
Source	<xs:attribute name="scalable" type="xs:boolean" use="optional"> <xs:annotation> <xs:documentation>Whether it is acceptable to scale the image.</xs:documentation> </xs:annotation> </xs:attribute>

Attribute NonLinear_type / @maintainAspectRatio

Namespace	No namespace
Annotations	Whether the ad must have its aspect ratio maintained when scales
Type	xs:boolean
Properties	use: optional
Used by	Complex Type NonLinear_type
Source	<xs:attribute name="maintainAspectRatio" type="xs:boolean" use="optional"> <xs:annotation> <xs:documentation>Whether the ad must have its aspect ratio maintained when scales</xs:documentation> </xs:annotation> </xs:attribute>

Attribute NonLinear_type / @minSuggestedDuration

Namespace	No namespace
Annotations	Suggested duration to display non-linear ad, typically for animation to complete. Expressed in standard time format hh:mm:ss
Type	xs:time
Properties	use: optional
Used by	Complex Type NonLinear_type
Source	<xs:attribute name="minSuggestedDuration" type="xs:time" use="optional">

	<pre> <xs:annotation> <xs:documentation>Suggested duration to display non-linear ad, typically for animation to complete. Expressed in standard time format hh:mm:ss</xs:documentation> </xs:annotation> </xs:attribute></pre>
--	--

Attribute NonLinear_type / @apiFramework

Namespace	No namespace
Annotations	The apiFramework defines the method to use for communication with the nonlinear element
Type	xs:string
Properties	use: optional
Used by	Complex Type NonLinear_type
Source	<pre> <xs:attribute name="apiFramework" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>The apiFramework defines the method to use for communication with the nonlinear element</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute Creative / Creatives / InLine / Ad / VAST / @id

Namespace	No namespace
Type	xs:string
Properties	use: optional
Used by	Element VAST/Ad/InLine/Creatives/Creative
Source	<pre><xs:attribute name="id" type="xs:string" use="optional"/></pre>

Attribute Creative / Creatives / InLine / Ad / VAST / @sequence

Namespace	No namespace
Annotations	The preferred order in which multiple Creatives should be displayed
Type	xs:integer
Properties	use: optional
Used by	Element VAST/Ad/InLine/Creatives/Creative
Source	<pre> <xs:attribute name="sequence" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>The preferred order in which multiple Creatives should be displayed</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute Creative / Creatives / InLine / Ad / VAST / @AdID

Namespace	No namespace
Annotations	Ad-ID for the creative (formerly ISCI)
Type	xs:string
Properties	use: optional
Used by	Element VAST/Ad/InLine/Creatives/Creative
Source	<pre> <xs:attribute name="AdID" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Ad-ID for the creative (formerly ISCI)</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute ClickTracking / VideoClicks / Linear / Creative / Creatives / Wrapper / Ad / VAST / @id

Namespace	No namespace
Type	xs:string

Properties	use:	optional
Used by	Element	VAST/Ad/Wrapper/Creatives/Creative/Linear/VideoClicks/ClickTracking
Source	<xs:attribute name="id" type="xs:string" use="optional"/>	

Attribute Creative / Creatives / Wrapper / Ad / VAST / @id

Namespace	No namespace
Type	xs:string
Properties	use: optional
Used by	Element VAST/Ad/Wrapper/Creatives/Creative
Source	<xs:attribute name="id" type="xs:string" use="optional"/>

Attribute Creative / Creatives / Wrapper / Ad / VAST / @sequence

Namespace	No namespace
Annotations	The preferred order in which multiple Creatives should be displayed
Type	xs:integer
Properties	use: optional
Used by	Element VAST/Ad/Wrapper/Creatives/Creative
Source	<xs:attribute name="sequence" type="xs:integer" use="optional"> <xs:annotation> <xs:documentation>The preferred order in which multiple Creatives should be displayed</xs:documentation> </xs:annotation> </xs:attribute>

Attribute Creative / Creatives / Wrapper / Ad / VAST / @AdID

Namespace	No namespace
Annotations	Ad-ID for the creative (formerly ISCI)
Type	xs:string
Properties	use: optional
Used by	Element VAST/Ad/Wrapper/Creatives/Creative
Source	<xs:attribute name="AdID" type="xs:string" use="optional"> <xs:annotation> <xs:documentation>Ad-ID for the creative (formerly ISCI)</xs:documentation> </xs:annotation> </xs:attribute>

Attribute Ad / VAST / @id

Namespace	No namespace
Type	xs:string
Properties	use: required
Used by	Element VAST/Ad
Source	<xs:attribute name="id" type="xs:string" use="required"/>

Attribute VAST / @version

Namespace	No namespace
Annotations	Current version is 2.0. The 2.0.1 version corrects an error in the Wrapper section related the Linear node's TrackingEvents and VideoCLicks elements.
Type	xs:string
Properties	use: required
Used by	Element VAST

Source	<pre><xs:attribute name="version" type="xs:string" use="required"> <xs:annotation> <xs:documentation>Current version is 2.0. The 2.0.1 version corrects an error in the Wrapper section related the Linear node's TrackingEvents and VideoCLicks elements.</ xs:documentation> </xs:annotation> </xs:attribute></pre>
--------	---